MULE PRO-FXR™ 1000





\$15,099



METALLIC SIERRA BLUE



POWER

Engine 4-stroke, 2-cylinder, DOHC, liquid-cooled, gas

999cc Displacement 61.5 lb-ft **Maximum Torque**

Bore x Stroke 92.0 x 75.1mm

Compression Ratio 10.1:1

Fuel System DFI® with 38mm throttle body

Continuously Variable Transmission (CVT) with (L,H,N,R) Transmission

Selectable 2WD/4WD, shaft Dual mode rear differential with **Final Drive**

differential lock

Engine Braking

(max)

Fuel Capacity 7.9 gal **Turning Radius** 14.0 ft

37.6 x 53.3 x 11.0 in **Cargo Bed** Dimensions (LxWxH)

Cargo Bed Load 999 lb / 600.0 lb CA Model Capacity

3

Payload Capacity

1,616.3 lb / 1,263.5 lb CA Model

1,735.3 lb* / 1,737.5 lb* CA Model

Multi-function display includes digital speedometer, fuel

2WD/4WD indicator, water temperature warning indicator, oil pressure warning indicator, fuel injection warning

indicator, CVT and EPS warning indicators, neutral, reverse

gauge, odometer, hour meter, clock, dual trip meters,

Seating Capacity

DETAILS

Overall Length

Overall Width

Overall Height

Curb Weight

Wheelbase

Towing Capacity 2,000 lb

Lighting (2) Halogen headlights. (2) LED headlights

122.0 in

64.0 in

77.2 in

Alternator Output 90 amp

CAPABILITY

Front Suspension / Double wishbone/11.0 in **Wheel Travel**

Rear Suspension / Wheel Travel

Double wishbone/10.1 in

Front Tires 27 x 9.00-12, radial **Rear Tires** 27 x 11.00-12, radial

Steering Electric Power Steering (EPS), Tilt steering

Independent, Mechanical Disc

Front Brakes Dual Disc, 2 piston caliper **Rear Brakes** Dual Disc, 1 piston caliper

Ground Clearance 13.2 in (max), 12.2 in (std)

Instruments

and parking indicators, seatbelt reminder lamps **Wheel Type**

Additional Features Rear Bumper, Contoured Two-Tone Bench Seat

Color Choices Metallic Sierra Blue

Warranty Kawasaki STRONG 3-Year Limited Warranty

Kawasaki Protection 12, 24, 36, or 48 months Plus™ (optional)

Scan with camera to view videos, key features and more.

Park Brake Type



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). All MULE™ PRO Series side x side's Rollover Protective Structure (ROPS) meets the performance requirements of ISO 3471.