²⁰²³ TERYX KRX[®] 1000 eS





^{MSRP} **\$22,699**



ICE GRAY/METALLIC ONYX BLACK



POWER

CAPABILITY Front Suspension / Wheel Travel

Rear Suspension / Wheel

Travel

Front Tires Rear Tires Steering Front Brakes Rear Brakes Ground Clearance Fuel Capacity Turning Radius

Scan with camera

to view videos,

key features

and more.

Ē.

Engine	4-stroke, DOHC, 8-valve parallel-twin, liquid cooled
Displacement	999cc
Maximum Torque	76.7 lb-ft @ 7,000 rpm
Bore x Stroke	92.0 x 75.1mm
Compression Ratio	11.5:1
Fuel System	DFI® with two 50mm throttle bodies
Ignition	TCBI with Electronic Advance
Starting System	Electric
Transmission	Automatic CVT with centrifugal clutch (H,L,N,R)
Final Drive	Selectable 2WD/4WD with locking front differential, shaft
Engine Braking	Yes

Cargo Bed Dimensions (LxWxH)	14.6 x 33.1 x 9.1 in	
Cargo Bed Load Capacity	351 lb	
Payload Capacity	781 lb	
Seating Capacity	2	
Towing Capacity	N/A	
Lighting	(2) LED headlights, (2) LED taillights, LED stoplight	
Standard Ground Clearance/Maximum Ground Clearance†	14.0 in (std) / 14.4 in (max)	

DETAILS

Automatic CVT with centrifugal clutch (H,L,N,R)		
Selectable 2WD/4WD with locking front differential, shaft	Frame	Ladder type, tubular steel
Yes	Overall Length	132.1 in
	Overall Width	68.1 in
	Overall Height	77.0 in
Double wishbone, FOX 2.5 Podium Live Valve Internal Bypass shocks	Curb Weight	1,944.8 lb* / 1,947.0 lb* CA Model
with piggyback reservoir, fully adjustable preload, and KECS controlled compression damping/18.6 in	Wheelbase	98.8 in
 4-link trailing-arm rear suspension, FOX 2.5 Podium Live Valve Internal Bypass shocks with piggyback reservoir, fully adjustable preload, and KECS controlled compression damping/21.1 in Maxxis® Carnivore 31 x 10.00R15 8PR Maxxis® Carnivore 31 x 10.00R15 8PR Electric Power Steering (EPS) / rack-and-pinion 	Instruments	Multi-function digital meter with bar-style tachometer (2 display options), digital speedometer, bar-style fuel gauge, gear indicator (L, H, N, R), Power Mode, driving mode (2WD/4WD/4WD+Diff Lock) indicator, Economical Riding Indicator, clock, odometer, dual trip meters, hour meter, water temperature, digital battery gauge, bar- style CTV temperature, seatbelt warning lamp, oil warning lamp, engine check lamp, water temperature warning lamp, neutral indicator lamp, reverse indicator lamp, parking indicator lamp, EPS warning lamp, and CVT belt warning lamp.
Dual hydraulic discs with two-piston calipers	Wheel Type	Alloy with bead-lock wheels
Dual hydraulic discs with single-piston calipers	Additional Features	Roof, Front Bumper
14.4 in (max), 14.0 in (std)	Color Choices	Ice Gray/Metallic Onyx Black
10.6 gal	Warranty	6 Month Limited Warranty
20.3 ft	Kawasaki Protection Plus™ (optional)	12, 24, or 36 months

*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). **When linked to a smartphone via Bluetooth, notification of call and messages received will be indicated on the instrument display. Note, compatibility is limited to iOS type smartphones.

†Maximum ground clearance is measured at maximum pre-load suspension setting.

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Warning: The Teryx[®] side x side can be hazardous to operate. For your safety: Always wear a helmet, eye protection and protective clothing. Never operate under the influence of drugs or alcohol. Avoid excessive speeds and stunt driving. Be extra careful on difficult terrain. Protect the environment. The Kawasaki Teryx side x side is an off-highway vehicle only, and is not designed, equipped or manufactured for use on public streets, roads or highways. ©2024 Kawasaki Motors Corp., U.S.A.

Specifications subject to change. Visit Kawasaki.com for full product details.