MULE PRO-FX™





\$12,999



SUPER BLACK



POWER

Engine 4-stroke, 3-cylinder, DOHC, liquid-cooled, gas

Displacement

Maximum Torque 48.0 lb-ft @ 3,500 rpm

Bore x Stroke 2.83x2.62 in

Compression Ratio 9.5:1

Fuel System DFI® with 34mm throttle body

Continuously Variable Transmission (CVT) with (H,L,N,R) Transmission

Selectable 2WD/4WD, shaft. Dual mode rear differential **Final Drive**

with differential lock

Engine Braking

Alternator Output 75 amp

(max)

Ground Clearance 10.4 in **Fuel Capacity** 7.9 gal

Turning Radius 16.0 ft

Cargo Bed

54.1 x 53.3 x 11.0 in **Dimensions (LxWxH)**

Cargo Bed Load

Capacity

999 lb / 600.0 lb CA Model

Payload Capacity 1,616.3 lb / 1,263.5 for CA Model

Seating Capacity

Towing Capacity 2,000 lb

Lighting (2) Halogen headlights.

CAPABILITY

Front Suspension / **Wheel Travel**

Double wishbone / 8.7 in

Rear Suspension / Wheel Travel

Double wishbone/8.5 in (L) /8.7 in (R)

Front Tires 26x9.00-12, radial **Rear Tires** 26x11.00-12, radial Steering Rack-and-pinion

Front Brakes Rear Brakes Dual Disc, 1 piston caliper

Park Brake Type

Dual Disc, 2 piston caliper

Independent, Mechanical Disc

DETAILS

Overall Length 133.3 in **Overall Width** 64.0 in **Overall Height** 77.4 in **Curb Weight** 1,816.9 lb* Wheelbase 92.3 in

Instruments

Multi-function display includes digital speedometer, fuel gauge, odometer, hour meter, clock, dual trip meters, 2WD/4WD indicator, water temperature warning indicator, oil pressure warning indicator, fuel injection warning indicator, CVT warning indicator, neutral, reverse and

parking indicators, seatbelt reminder lamps

Wheel Type Steel

Color Choices Super Black

Warranty Kawasaki STRONG 3-Year Limited Warranty

Kawasaki Protection Plus™ (optional)

12, 24 or 36 months

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). All MULE™ PRO Series side x side's Rollover Protective Structure (ROPS) meets the performance requirements of ISO 3471