MULE PRO-FXT™ EPS





\$15,899



BRIGHT WHITE



TIMBERLINE GREEN



POWER

Engine 4-stroke, 3-cylinder, DOHC, liquid-cooled, gas

Displacement 812cc

Maximum Torque 48.0 lb-ft @ 3,500 rpm

2.83x2.62 in **Bore x Stroke**

Compression Ratio 9.5:1

DFI® with 34mm throttle body **Fuel System**

Continuously Variable Transmission (CVT) with (H,L,N,R) **Transmission**

Final Drive Selectable 2WD/4WD, shaft. Dual mode rear differential

with differential lock

Engine Braking Yes

Alternator Output

75 amp

(max)

CAPABILITY

Front Suspension / **Wheel Travel**

Rear Suspension /

Double wishbone/8.5 (L) /8.7 (R) in

Double wishbone/8.7 in

Wheel Travel **Front Tires**

26x9.00-12, radial

Rear Tires 26x11.00-12, radial

Steering Electric Power Steering (EPS), Tilt steering

Front Brakes

Dual Disc, 2 piston caliper

Rear Brakes

Dual Disc, 1 piston caliper

Park Brake Type

Independent, Mechanical Disc

Ground Clearance

10.2 in

Fuel Capacity 7.9 gal **Turning Radius**

Cargo Bed

Dimensions (LxWxH)

Cargo Bed Load Capacity

Payload Capacity

Seating Capacity

Towing Capacity

Lighting

16.0 ft

42.7 x 53.7 x 11.0 in (3-person) / 22.0 x 53.7 x 11.0 in (6-

999 lb (3-person) / 350 lb (6-person) / 348 lb CA Model

1,616.3 lb / 1,263.5 lb CA Model 3-person (1 row), 6 person (2 row)

2,000 lb

(2) Halogen headlights.

DETAILS

Overall Length 133.3 in

Overall Width 64.0 in

Overall Height 77.6 in

Curb Weight 1,911.7 lb*

Wheelbase 92.3 in

Instruments

Multi-function display includes digital speedometer, fuel gauge, odometer, hour meter, clock, dual trip meters,

2WD/4WD indicator, water temperature warning indicator, oil pressure warning indicator, fuel injection warning indicator, CVT and EPS warning indicators, neutral, reverse

and parking indicators, seatbelt reminder lamps

Wheel Type Steel

Color Choices

Timberline Green, Bright White

Warranty

Kawasaki STRONG 3-Year Limited Warranty

Kawasaki Protection Plus™ (optional)

12, 24 or 36 months

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). All MULE SX™ Series side x side's Rollover Protective Structure (ROPS) meets the performance requirements of SAE J1194.