MULE PRO-MX™ EPS LE





\$14,199



SUPER BLACK



POWER

Engine 4-stroke, single cylinder, SOHC, 4-valve liquid-cooled

Displacement

Maximum Torque 42.7 lb-ft @ 5,000 rpm

102.0 x 85.0 mm Bore x Stroke

Compression Ratio 10.3:1

Fuel System DFI® with 44mm throttle body

Continuously Variable Transmission (CVT) with centrifugal **Transmission**

Final Drive Selectable 2WD/4WD, shaft. Dual mode rear differential

with differential lock

Engine Braking

Alternator Output 35.7 amp

(max)

Fuel Capacity 9.5 gal

Turning Radius 14.0 ft

Cargo Bed

Dimensions (LxWxH)

1,200 lb

Cargo Bed Load Capacity

Payload Capacity

699 lb / 600 lb CA Model

33.4 x 44.1 x 9.1 in

Seating Capacity

Towing Capacity 1,500 lb

Lighting (2) Halogen headlights. (2) LED headlights

CAPABILITY

Front Suspension / Double wishbone/8.6 in

Rear Suspension / Wheel Travel

Wheel Travel

Double wishbone/9.1 in

Front Tires 25x10.00-12, radial

Rear Tires 25x10.00-12, radial

Electric Power Steering (EPS), Tilt steering Steering

Independent, Mechanical Disc

Front Brakes Dual Disc, 2 piston caliper **Rear Brakes** Dual Disc, 1 piston caliper

Ground Clearance 10.6 in **DETAILS Overall Length**

110.0 in

Overall Width 60.0 in

Overall Height 75.8 in

Curb Weight 1,594.2 lb*

Wheelbase 78.9 in

Instruments

Multi-function display includes digital speedometer, fuel gauge, odometer, hour meter, clock, dual trip meters, 2WD/4WD indicator, water temperature warning indicator, EPS warning indicators, neutral, reverse and parking indicators, differential indicator lamp, seatbelt reminder

lamps

Wheel Type

Additional Features Roof, Cast Aluminum Wheels

Color Choices Super Black

Warranty Kawasaki STRONG 3-Year Limited Warranty

Kawasaki Protection Plus™ (optional)

12, 24 or 36 months

Scan with camera to view videos, key features and more.

Park Brake Type



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). All MULE™ PRO Series side x side's Rollover Protective Structure (ROPS) meets the performance requirements of ISO 3471