MULE PRO-MX™ SE





MSRP **\$14,699**



GALAXY SILVER



POWER

Engine 4-stroke, single cylinder, SOHC, 4-valve liquid-cooled

Displacement 695c

Maximum Torque 42.7 lb-ft @ 5,000 rpm

Bore x Stroke 102.0 x 85.0 mm

Compression Ratio 10.3:1

Fuel System DFI® with 44mm throttle body

Transmission Continuously Variable Transmission (CVT) with centrifugal

clutch, (H,L,N,R)

Final Drive Selectable 2WD/4WD, shaft. Dual mode rear differential

with differential lock

Engine Braking Ye

Alternator Output 35.7 amp

(max)

Payload Capacity
Seating Capacity

Cargo Bed Load

Fuel Capacity

Turning Radius

Cargo Bed Dimensions (LxWxH)

Capacity

Towing Capacity

Lighting

1,500 lb

1,200 lb

9.5 gal

14.0 ft

33.4 x 44.1 x 9.1 in

699 lb / 600 lb CA Model

(2)

(2) Halogen headlights. (2) LED headlights

CAPABILITY

Front Suspension / Double wishbone/8.6 in Wheel Travel

Rear Suspension / Wheel Travel Double wishbone/9.1 in

Wheel Travel

25x10.00-12, radial

Rear Tires 25x10.00-12, radial

Electric Power Steering (EPS), Tilt steering

Front Brakes

Front Tires

Steering

Dual Disc, 2 piston caliper

Rear Brakes

Dual Disc, 1 piston caliper

Park Brake Type

Independent, Mechanical Disc

Ground Clearance 10.6 in

DETAILS

Overall Length

111.4 in

Overall Width 60.0 in

Overall Height 75.8 in

Curb Weight 1,622.9 lb*

Wheelbase 78.9 in

Instruments

Multi-function display includes digital speedometer, fuel gauge, odometer, hour meter, clock, dual trip meters, 2WD/4WD indicator, water temperature warning indicator,

EPS warning indicators, neutral, reverse and parking indicators, differential indicator lamp, seatbelt reminder

lamps

Wheel Type Alloy

Additional Features

Roof, Winch, Cast Aluminum Wheels, Painted Body Panels

Color Choices Galaxy Silver

Warranty

Kawasaki STRONG 3-Year Limited Warranty

Kawasaki Protection Plus™ (optional) 12, 24 or 36 months

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). All MULE™ PRO Series side x side's Rollover Protective Structure (ROPS) meets the performance requirements of ISO 3471.