TERYX KRX® 1000





\$20,199



LIME GREEN/METALLIC ONYX BLACK



SUNBEAM RED/METALLIC ONYX BLACK



POWER

Engine 4-stroke, DOHC, 8-valve parallel-twin, liquid cooled

Displacement 999cc

Maximum Torque 76.7 lb-ft @ 7,000 rpm

Bore x Stroke 92.0 x 75.1mm

Compression Ratio 11.5:1

DEI® with two 50mm throttle hodies **Fuel System**

Ignition TCBI with Electronic Advance

Starting System Electric

Automatic CVT with centrifugal clutch (H,L,N,R) **Transmission**

Final Drive Selectable 2WD/4WD with locking front differential, shaft

Engine Braking Yes

CAPABILITY

Front Suspension / Wheel Travel

Wheel Travel

Double wishbone, FOX 2.5 PODIUM LSC shocks with piggyback reservoir, fully adjustable preload, and 24-position adjustable

compression damping/18.6 in

Rear Suspension /

4-link trailing-arm rear suspension, FOX 2.5 PODIUM LSC shocks with piggyback reservoir, fully adjustable preload, and 24-

position adjustable compression damping/21.1 in

Front Tires Maxxis® Carnivore 31 x 10.00R15 8PR

Rear Tires Maxxis® Carnivore 31 x 10.00R15 8PR

Steering Electric Power Steering (EPS) / rack-and-pinion

Front Brakes Dual hydraulic discs with two-piston calipers

Rear Brakes Dual hydraulic discs with single-piston calipers

Ground Clearance 14.8 in (max), 14.2 in (std)

Fuel Capacity 10.6 gal **Turning Radius** 20.3 ft

Cargo Bed Dimensions 14.6 x 33.1 x 9.1 in (LxWxH)

Cargo Bed Load

Capacity

351 lb

2

Payload Capacity 781 lb

Seating Capacity

Towing Capacity N/A

(2) LED headlights, (2) LED taillights, LED stoplight Lighting

DETAILS

Frame Ladder type, tubular steel

Overall Length 130.1 in Overall Width 68.1 in **Overall Height** 74.8 in

1,896.3 lb* / 1,898.5 lb* CA Model **Curb Weight**

Wheelbase 98.8 in

Instruments Multi-function digital meter with bar-style tachometer (2 display

options), digital speedometer, bar-style fuel gauge, gear indicator (L, H, N, R), Power Mode, driving mode (2WD/4WD/4WD +Diff Lock) indicator, Economical Riding Indicator, clock, odometer, dual trip meters, hour meter, water temperature, digital battery gauge, bar-style CTV temperature, seatbelt warning lamp, oil warning lamp, engine check lamp, water temperature warning lamp, neutral indicator lamp, reverse indicator lamp, parking indicator lamp, EPS warning lamp, and

CVT belt warning lamp.

Wheel Type Alloy with bead-lock wheels

Color Choices Lime Green/ Metallic Onyx Black, Sunbeam Red/Metallic Onyx

6 Month Limited Warranty Warranty

Kawasaki Protection 12, 24, or 36 months Plus™ (optional)

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Warning: The Teryx® side x side can be hazardous to operate. For your safety: Always wear a helmet, eye protection and protective clothing. Never operate under the influence of drugs or alcohol. Avoid excessive speeds and stunt driving. Be extra careful on difficult terrain. Protect the environment. The Kawasaki Teryx side x side is an off-highway vehicle only, and is not designed, equipped or manufactured for use on public streets, roads or highways. ©2024 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit Kawasaki.com for full product details.