TERYX® S LE





MSRP \$14,999



METALLIC ELECTRIC TURQUOISE/SUPER BLACK



NEON RED/SUPER BLACK



27.6 x 43.3 x 10.4 in

POWER

4-stroke, SOHC, 4-valve V-twin, liquid-cooled **Engine**

Displacement 783cc

Maximum Torque 47.0 lb-ft@ 5,500 rpm

Bore x Stroke 85.0 x 69.0mm

Compression Ratio 10.7:1

DEI® with two 36mm Mikuni throttle hodies **Fuel System**

Ignition TCBI with Electronic Advance

Electric **Starting System**

Transmission Automatic CVT with centrifugal clutch (H,L,N,R)

Selectable 2WD/4WD with locking front differential, shaft **Final Drive**

Engine Braking

Cargo Bed Dimensions (LxWxH)

Cargo Bed Load 600 lh

Capacity

Payload Capacity 1,100 lb

Seating Capacity

Towing Capacity 1.300 lb

Lighting (4) LED headlights, (2) incandescent taillights, incandescent

stoplight

Standard Ground Clearance/Maximum **Ground Clearancet**

11.2 in / 12.2 in

CAPABILITY

Front Suspension / Wheel Travel

Double wishbone, FOX 2.0 LSC Piggyback Shocks, fully adjustable preload, and adjustable compression damping/10.7

Rear Suspension / Wheel Travel

Double wishbone, FOX 2.0 LSC Piggyback Shocks, fully adjustable preload, and adjustable compression damping/10.0

Front Tires Maxxis® 27 x 9-14

Maxxis® 27 x 11-14 **Rear Tires**

Electric Power Steering (EPS) / rack-and-pinion Steering Front Brakes Dual hydraulic discs with two-piston calipers

Rear Brakes Sealed, oil-bathed, multi-disc

Ground Clearance 11.2 in / 12.2 in

Fuel Capacity 7.9 gal **Turning Radius** 17.7 ft

DETAILS

Frame

Steel Tube Double-X Reinforcement

Overall Length 118.1 in **Overall Width** 62.2 in **Overall Height** 78.5 in **Curb Weight** 1,596.4 lb*

Wheelbase 88.2 in

Multi-function digital meter with speedometer, fuel gauge, Instruments

clock, hour meter, odometer, dual trip meter and parking-brake indicator, R/N/P/4WD, water temp and low-oil-pressure

indicators

Wheel Type Alloy

Additional Features Roof

Color Choices Neon Red/Super Black, Metallic Electric Turquoise/Super Black

Warranty Kawasaki Strong 3-Year Limited Warranty

Kawasaki Protection 12, 24, or 36 months Plus™ (optional)

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Warning: The Teryx® side x side can be hazardous to operate. For your safety: Always wear a helmet, eye protection and protective clothing. Never operate under the influence of drugs or alcohol. Avoid excessive speeds and stunt driving. Be extra careful on difficult terrain. Protect the environment. The Kawasaki Teryx side x side is an off-highway vehicle only, and is not designed, equipped or manufactured for use on public streets, roads or highways. ©2024 Kawasaki Motors Corp., U.S.A.