JET SKI® SX-R™ 160





MSRP \$11,999





D	n	V	V	Г	D
Г	u	ľ	v	E	П

Engine 4-stroke, DOHC, four valves per cylinder, 4-

cylinder inline

Displacement 1,498cc

Bore x Stroke 83.0 x 69.2mm

Compression

Ratio

10.6:1

Induction Naturally aspirated

Maximum Boost N/A

Cooling System Inducted water

DFI® with 60mm throttle body **Fuel System**

TCBI with Digital Advance Ignition

Starting System Electric

Propulsion System

148mm jet pump, axial-flow, single stage

Impeller 3-blade, oval-edge stainless steel

PERFORMANCE

Coupling Direct drive from engine

Oil Capacity 5.3 qt

Fuel Capacity 6.1 gal

Load Capacity 1-person

N/A **Storage Capacity**

DETAILS

Overall Length 104.5 in

Overall Width 30.1 in

Overall Height 33.1 in

Curb Weight 551.3 lb*

Seating

Capacity

Color Choices

Warranty

Kawasaki **Protection** Plus™ (optional)

1

Ebony/Ice Gray

12 Month Limited Warranty

12, 24, 36, or 48 months



Lubrication Semi-dry sump system

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Ride responsibly. Kawasaki believes safety begins with us and continues with you. Always wear a USCG-approved personal flotation device, eyewear, gloves, footwear, and a wet suit or clothing that provides equivalent protection (board shorts with neoprene liner). Never ride under the influence of drugs or alcohol. Respect the rights of shoreline residents and other marine recreationists. Boat smart from the start. Take a Boating Safety course; for more information visit www.USCGBoating.org. Jet Ski watercraft are inboard powerboats and their use is subject to all applicable federal, state, and local boating laws. Read Owner's Manual and all on-product warnings. ©2024 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit Kawasaki.com for full product details.