## NEW 2024 KLX®230 S







POWER		Rear Brakes	Single 220mm petal disc with single-piston caliper (and ABS)
Engine Displacement	4-stroke single, SOHC, air-cooled	DETAILS	
Bore x Stroke Compression Ratio	67.0 x 66.0mm 9.4:1	Frame Type Rake/Trail Overall Length	Perimeter, high-tensile steel 24.6°/3.7 in 81.8 in
Maximum Torque Fuel System	13.2 lb-ft @ 6,400 rpm DFI® with dual 32mm throttle bodies	Overall Width Overall Height	33.2 in 44.8 in
Ignition Transmission	TCBI with Electronic Advance 6-speed	Ground Clearance	9.4 in
Final Drive Electronic Rider Aids	Sealed chain Anti-lock Brake System (ABS)	Seat Height Curb Weight	33.2 in 291.0/293.2 lb* 50-State Model
PERFORMANCE		Fuel Capacity Wheelbase	2.0 gal 53.7 in
Front Suspension	37mm telescopic fork/7.8 in	Special Features	ERGO-FIT <sup>®</sup> , LCD Instrumentation with Smartphone Connectivity via RIDEOLOGY THE

Front Suspension / Wheel Travel	37mm telescopic fork/7.8 in		
Rear Suspension / Wheel Travel	Uni-Trak® linkage system and single shock with adjustable spring preload/8.7 in		
Front Tire	2.75 x 21		
Rear Tire	4.10 x 18		
Front Brakes	Single 240mm (265mm ABS Model) petal disc with a dual-piston caliper (and ABS)		

\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). When equipped, California evaporative emissions equipment adds approximately 2.2 lb.

**Color Choices** 

Warranty

Kawasaki

Protection Plus™ (optional) APP MOTORCYCLE

Lime Green, Battle Gray

12, 24, 36 or 48 months

12 Month Limited Warranty

Scan with camera to view videos, key features and more.



KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2024 Kawasaki Motors Corp., U.S.A.

Specifications subject to change. Visit Kawasaki.com for full product details.