UPDATED 2024

MULE PRO-MX™ SE





MSRP **\$15,499**



GALAXY SILVER



POWFR

Engine 4-stroke, single cylinder, SOHC, 4-valve liquid-cooled

Displacement 695cc

Maximum Torque 42.7 lb-ft @ 5,000 rpm

Bore x Stroke 102.0 x 85.0mm

Compression Ratio 10.3:

Fuel System DFI® with 44mm throttle body

Transmission Continuously Variable Transmission (CVT) with centrifugal

clutch, (H,L,N,R)

Final Drive Selectable 2WD/4WD, shaft Dual mode rear differential with

differential lock

Engine Braking Yes

Alternator Output 35.7 amp

(max)

Fuel Capacity 9.5 gal
Turning Radius 14.0 ft

Cargo Bed 33.4 x 44.1 x 9.1 in

Dimensions (LxWxH)

Cargo Bed Load 699 lb / 600 lb CA Model Capacity

Payload Capacity 1,200 lb

Seating Capacity 2

DETAILS

Towing Capacity 1,500 lb

Lighting (2) Halogen headlights. (2) LED headlights

CAPABILITY

Front Suspension / Double wishbone/8.6 in Wheel Travel

Rear Suspension / Double wishbone/9.1 in Wheel Travel

 Front Tires
 25 x 10.00-12, radial

 Rear Tires
 25 x 10.00-12, radial

Steering Electric Power Steering (EPS), Tilt steering

Front Brakes

Dual Disc, 2 piston caliper

Rear Brakes

Dual Disc, 1 piston caliper

Park Brake Type

Independent, Mechanical Disc

Ground Clearance 10.6 in

Overall Length 111.4 in

Overall Width 60.0 in

Overall Height 75.8 in

Curb Weight 1,622.9 lb* / 1,625.1 lb* CA Model

Wheelbase 78.9 in

Instruments Multi-function display includes digital speedometer, fuel gauge, odometer, hour meter, clock, dual trip meters,

SAUD/4WD indicator, water temperature warning indicator, EPS warning indicators, neutral, reverse and parking indicators, differential indicator lamp, seatbelt reminder

lamps

Wheel Type Alloy

Additional Features Roof, WARN® VRX 35 Winch, Cast Aluminum Wheels, Painted

Body Panels

Color Choices Galaxy Silver

Warranty Kawasaki STRONG 3-Year Limited Warranty

Kawasaki Protection 12, 24, 36, or 48 months Plus™ (optional)

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). All MULE™ PRO Series side x side's Rollover Protective Structure (ROPS) meets the performance requirements of ISO 3471.