MULE PRO-FXT™ RANCH EDITION





\$17,299



METALLIC PHANTOM SILVER



POWER

Engine 4-stroke, 3-cylinder, DOHC, liquid-cooled, gas

Displacement 812cc

Maximum Torque 48.0 lb-ft @ 3500 rpm

Bore x Stroke 2.83x2.62 in

Compression Ratio

Fuel System DFI® with 34mm throttle body

Transmission Continuously Variable Transmission (CVT) with (H,L,N,R)

Final Drive Selectable 2WD/4WD, shaft. Dual mode rear differential

with differential lock

Engine Braking

Alternator Output 75 amp

(max)

CAPABILITY

Double wishbone/8.7 in Front Suspension / Wheel Travel

Rear Suspension / Double wishbone/8.5 (L) /8.7 (R) in **Wheel Travel**

Front Tires 26x9.00-12, radial **Rear Tires** 26x11.00-12, radial

Steering Electric Power Steering (EPS), Tilt steering

Front Brakes Dual Disc, 2 piston caliper **Rear Brakes** Dual Disc, 1 piston caliper

Park Brake Type Independent, Mechanical Disc **Ground Clearance** 10.0 in

Turning Radius 16.0 ft

Fuel Capacity

Capacity

Cargo Bed 42.7 x 53.7 x 11.0 in (3-person)22.0 x 53.7 x 11.0 in (6-

Dimensions (LxWxH)

Cargo Bed Load 1000 lb (3-person)350 lb (6-person)(600 lb for California

models)

7.9 gal

1574 lb **Payload Capacity**

Seating Capacity 3-person (1 row), 6 person (2 row)

Towing Capacity 2000 lb

Lighting (2) Halogen headlights. (2) LED headlights

DETAILS

Overall Length 135.6 in **Overall Width** 64.0 in 79.5 in **Overall Height Curb Weight** 1971.3 lb*

Wheelbase 92.3 in

Instruments Multi-function display includes digital speedometer, fuel

> gauge, odometer, hour meter, clock, dual trip meters, 2WD/4WD indicator, water temperature warning indicator, oil pressure warning indicator, fuel injection warning indicator, CVT and EPS warning indicators, neutral, reverse and parking indicators, seatbelt

reminder lamps

Wheel Type

Metallic Phantom Silver Color Choices

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). All MULE™ PRO Series side x side's Rollover Protective Structure (ROPS) meets the performance requirements of ISO 3471.