2023 **KLR®650 ADVENTURE**





Let the Good Times Roll®

POWER		Rear Suspension / Wheel Travel	Uni-Trak® single shock with adjustable rebound damping and adjustable spring preload/ 7.3 in
Engine	4-Stroke, single cylinder, DOHC	Front Tire	90/90-21
Displacement	652cc	Rear Tire	130/80-17
Bore x Stroke	100.0 x 83.0mm	Front Brakes	Single 300mm disc with 2-piston calipers (and ABS)
Compression Ratio	9.8:1	Rear Brakes	Single 240mm disc with single-piston caliper (and ABS)
Maximum Torque	39.1 lbft. @ 4,500rpm		
Fuel System	DFI® with 40mm throttle body	DETAILS	
	bir with some inotice body		
Ignition	CDI	Frame Type	Tubular, semi-double cradle
Ignition Transmission			Tubular, semi-double cradle 30.0°/4.8 in
-	CDI 5-speed, return shift with wet multi-disc	Frame Type	
Transmission	CDI 5-speed, return shift with wet multi-disc manual clutch	Frame Type Rake/Trail	30.0°/4.8 in
Transmission Final Drive	CDI 5-speed, return shift with wet multi-disc manual clutch Sealed chain	Frame Type Rake/Trail Overall Length	30.0°/4.8 in 89.8 in

PERFORMANCE

Front Suspension / Wheel Travel 41mm telescopic fork/ 7.9 in

Frame Type	Tubular, semi-double cradle
Rake/Trail	30.0°/4.8 in
Overall Length	89.8 in
Overall Width	38.2 in
Overall Height	57.3/55.9 in (screen hi/lo)
Ground Clearance	8.3 in
Seat Height	34.3 in
Curb Weight	487.1 lb* (ABS), 482.7 lb* (non-ABS)
Fuel Capacity	6.1 gal
Wheelbase	60.6 in
Color Choices	Cypher Camo Gray (Matte)



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). When equipped, California evaporative emissions equipment adds approximately 2.2 lb.

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit Kawasaki.com for full product details.