²⁰²³ MULE PRO-FX[™] EPS







POWER

| Engine | 4-stroke, 3-cylinder, DOHC, liquid-cooled, gas |
|----------------------------|---|
| Displacement | 812cc |
| Maximum Torque | 48.0 lb-ft @ 3,500 rpm |
| Bore x Stroke | 2.83x2.62 in |
| Compression Ratio | 9.5:1 |
| Fuel System | DFI® with 34mm throttle body |
| Transmission | Continuously Variable Transmission (CVT) with (H,L,N,R) |
| Final Drive | Selectable 2WD/4WD, shaft. Dual mode rear differential with differential lock |
| Engine Braking | Yes |
| Alternator Output (max) | 75 amp |

CAPABILITY

Scan with camera

to view videos,

key features

and more.

| | | overaumeight | //.¬ |
|------------------------------------|--|---------------|------------|
| Front Suspension / Wheel Travel | Double wishbone/8.7 in | Curb Weight | 1,83 |
| Rear Suspension / Wheel Travel | Double wishbone/8.5 in (L) /8.7 in (R) | Wheelbase | 92.3 |
| wheet havet | | Instruments | Mu |
| Front Tires | 26x9.00-12, radial | | fue met |
| Rear Tires | 26x11.00-12, radial | | ind |
| Steering | Electric Power Steering (EPS), Tilt steering | | war neu |
| Front Brakes | Dual Disc, 2 piston caliper | | ren |
| Rear Brakes | Dual Disc, 1 piston caliper | Wheel Type | Ste |
| Park Brake Type | Independent, Mechanical Disc | Color Choices | Tim |
| | | | |

| Ground Clearance | 10.4 in |
|---------------------------------|-----------------------------------|
| Fuel Capacity | 7.9 gal |
| Turning Radius | 16.0 ft |
| Cargo Bed Dimensions (LxWxH) | 54.1 x 53.3 x 11.0 in |
| Cargo Bed Load Capacity | 999 lb / 600.0 lb CA Model |
| Payload Capacity | 1,616.3 lb / 1,263.5 for CA Model |
| Seating Capacity | 3 |
| Towing Capacity | 2,000 lb |
| Lighting | (2) Halogen headlights. |

DETAILS

| Overall Length | 133.3 in |
|--------------------|--|
| Overall Width | 64.0 in |
| Overall Height | 77.4 in |
| Curb Weight | 1,830.2 lb* |
| Wheelbase | 92.3 in |
| Instruments | Multi-function display includes digital speedometer, fuel gauge, odometer, hour meter, clock, dual trip meters, 2WD/4WD indicator, water temperature warning indicator, oil pressure warning indicator, fuel injection warning indicator, CVT and EPS warning indicators, neutral, reverse and parking indicators, seatbelt reminder lamps |
| Wheel Type | Steel |
| Color Choices | Timberline Green, Bright White |
| | |

*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

All MULETM PRO Series side x side's Rollover Protective Structure (ROPS) meets the performance requirements of ISO 3471.

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear protective gear appropriate for the use of this vehicle. Never operate under the influence of drugs or alcohol. Protect the environment. The Kawasaki MULE™ side x side is an off- highway vehicle only, and is not designed, equipped or manufactured for use on public streets, roads or highways. Obey the laws and regulations that control the use of your vehicle. ©2024 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit Kawasaki.com for full product details.