MULE PRO-FXT™





MSRP **\$14,399**



SUPER BLACK



POWER

Engine 4-stroke, 3-cylinder, DOHC, liquid-cooled, gas

Displacement 812cc

Maximum Torque 48.0 lb-ft @ 3,500 rpm

Bore x Stroke 2.83x2.62 in

Compression Ratio 9.5:1

Fuel System DFI® with 34mm throttle body

Transmission Continuously Variable Transmission (CVT) with (H,L,N,R)

Final Drive Selectable 2WD/4WD, shaft. Dual mode rear differential

with differential lock

Engine Braking Ye

Alternator Output 75 amp

(max)

Ground Clearance 10.2 in

Fuel Capacity 7.9 gal

Turning Radius 16.0 ft

Cargo Bed

Dimensions (LxWxH)

Cargo Bed Load

Capacity

Payload Capacity

Seating Capacity

ocuting cupacity

Towing Capacity

Lighting

1,616.3 lb / 1,263.5 lb CA Model

person)

3-person (1 row), 6 person (2 row)

42.7 x 53.7 x 11.0 in (3-person) / 22.0 x 53.7 x 11.0 in (6-

999 lb (3-person) / 350 lb (6-person) / 348 lb CA Model

2,000 lb**

(2) Halogen headlights.

CAPABILITY

Front Suspension / Wheel Travel Double wishbone/8.7 in

Rear Suspension /

Double wishbone/8.5 in (L) /8.7 in (R)

Wheel Travel
Front Tires

26x9.00-12, radial

Rear Tires

26x11.00-12, radial

Steering

Rack-and-pinion

Front Brakes

Dual Disc, 2 piston caliper

Dual Disc, 1 piston caliper

Rear Brakes
Park Brake Type

Independent, Mechanical Disc

DETAILS

Overall Length 133.3 in

Overall Width 64.0 in

Overall Height 77.6 in

Curb Weight 1,887.5 lb*

Wheelbase 92.3 in

Instruments Multi-function display includes digital speedometer,

fuel gauge, odometer, hour meter, clock, dual trip meters, 2WD/4WD indicator, water temperature warning indicator, oil pressure warning indicator, fuel injection warning indicator, CVT warning indicator, neutral, reverse and parking indicators, seatbelt reminder lamps

Wheel Type Steel

Color Choices Super Black

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). All MULE™ PRO Series side x side's Rollover Protective Structure (ROPS) meets the performance requirements of ISO 3471.