

2023

MULE PRO-FXT™ RANCH EDITION PLATINUM



MSRP


\$20,099

 METALLIC RUSTIC BRONZE



POWER		Turning Radius	16.0 ft
Engine	4-stroke, 3-cylinder, DOHC, liquid-cooled, gas	Cargo Bed Dimensions (LxWxH)	42.7 x 53.7 x 11.0 in (3-person) / 22.0 x 53.7 x 11.0 in (6-person)
Displacement	812cc	Cargo Bed Load Capacity	999 lb (3-person) / 350 lb (6-person) / 348 lb CA Model
Maximum Torque	48.0 lb-ft @ 3,500 rpm	Payload Capacity	1,616.3 lb / 1,263.5 lb CA Model
Bore x Stroke	2.83x2.62 in	Seating Capacity	3-person (1 row), 6 person (2 row)
Compression Ratio	9.5:1	Towing Capacity	2,000 lb
Fuel System	DFI® with 34mm throttle body	Lighting	(2) Halogen headlights. (2) LED headlights
Transmission	Continuously Variable Transmission (CVT) with (H,L,N,R)	DETAILS	
Final Drive	Selectable 2WD/4WD, shaft. Dual mode rear differential with differential lock	Overall Length	140.2 in
Engine Braking	Yes	Overall Width	64.0 in
Alternator Output (max)	75 amp	Overall Height	79.5 in
CAPABILITY		Curb Weight	2,035.2 lb*
Front Suspension / Wheel Travel	Double wishbone/8.7 in	Wheelbase	92.3 in
Rear Suspension / Wheel Travel	Double wishbone/8.5 (L) / 8.7 (R) in	Instruments	Multi-function display includes digital speedometer, fuel gauge, odometer, hour meter, clock, dual trip meters, 2WD/4WD indicator, water temperature warning indicator, oil pressure warning indicator, fuel injection warning indicator, CVT and EPS warning indicators, neutral, reverse and parking indicators, seatbelt reminder lamps
Front Tires	26x9.00-12, radial	Wheel Type	Alloy
Rear Tires	26x11.00-12, radial	Additional Features	Roof, WARN® VRX 45 Winch, Premium Seats, Premium Shoulder Pads, Quad LED Headlights, Front Brush Guard, Headlight Guards, Rear Bumper, Anti-cinch Seatbelts, Additional Under Seat Storage Bin, Rearview Mirror
Steering	Electric Power Steering (EPS), Tilt steering	Color Choices	Metallic Rustic Bronze
Front Brakes	Dual Disc, 2 piston caliper	Warranty	Kawasaki STRONG 3-Year Limited Warranty
Rear Brakes	Dual Disc, 1 piston caliper	Kawasaki Protection Plus™ (optional)	12, 24 or 36 months
Park Brake Type	Independent, Mechanical Disc		
Ground Clearance	10.0 in		
Fuel Capacity	7.9 gal		

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). All MULE™ PRO Series side x side's Rollover Protective Structure (ROPS) meets the performance requirements of ISO 3471. WARN®? VRX 45, the WARN logo and THE RED HOOK STRAP are registered trademarks of Warn Industries, Inc. KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear protective gear appropriate for the use of this vehicle. Never operate under the influence of drugs or alcohol. Protect the environment. The Kawasaki MULE™ side x side is an off- highway vehicle only, and is not designed, equipped or manufactured for use on public streets, roads or highways. Obey the laws and regulations that control the use of your vehicle. ©2024 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit Kawasaki.com for full product details.