NINJA® ZX™-6R KRT EDITION





MSRP NON-ABS \$10,999

MSRP ABS \$11,999



LIME GREEN/EBONY



D	n	M	IC	D
Г	U	W	ľ	П

Engine 4-stroke, In-Line Four, DOHC, 16-valve, liquid-

cooled

Displacement 636cc

Bore x Stroke 67.0 x 45.1mm

Compression

Ratio

12.9:1

DFI® with 38mm Keihin throttle bodies (4) and **Fuel System**

oval sub-throttles

Ignition TCBI with Digital Advance

6-speed, return shift **Transmission**

Final Drive Sealed chain

Electronic Rider

Aids

Kawasaki TRaction Control (KTRC), Power Mode, Kawasaki Intelligent anti-lock Brake System (KIBS) (ABS only), Kawasaki Quick Shifter (KQS) (upshift

PERFORMANCE

Front Suspension / Wheel Travel

41mm inverted Showa SFF-BP fork with top-out springs, stepless compression and rebound damping, adjustable spring preload/4.7 in

Rear Suspension / Wheel Travel

Bottom-link Uni-Trak® with gas-charged shock, stepless compression damping adjustment, 25way adjustable rebound damping, fully adjustable spring preload/5.9 in

Front Tire 120/70 ZR17 **Rear Tire** 180/55 ZR17

Front Brakes Dual 310mm petal discs with dual radial-

mounted, Nissin 4-piston, monobloc calipers, Kawasaki Intelligent anti-lock Brake System (KIBS)

(ABS only)

Rear Brakes Single 220mm petal discs with single-piston

caliper, Kawasaki Intelligent anti-lock Brake

System (KIBS) (ABS only)

DETAILS

Frame Type Aluminum perimeter

23.5°/4.0 in Rake/Trail

Overall Length 79.7 in

Overall Width 28.0 in

Overall Height 43.3 in

Ground Clearance 5.1 in

Seat Height 32.7 in

Curb Weight 430.0 lb* (ABS), 425.6 lb* (non-ABS)

Fuel Capacity 4.5 gal

Wheelbase 55.1 in

Color Choices Lime Green/Ebony

Warranty 12 Month Limited Warranty

Kawasaki 12, 24, 36 or 48 months **Protection Plus™**





(optional)