TERYX KRX®4 1000 SE





\$24,499

LIME GREEN/METALLIC ONYX BLACK



Cargo Bed Dimensions

(LxWxH)

Capacity

Cargo Bed Load

Payload Capacity

Seating Capacity

Towing Capacity

SUNBEAM RED/METALLIC ONYX BLACK



14.6 x 33.1 x 9.1 in

351 lb

1,001 lb

N/A

POWER

4-stroke, DOHC, 8-valve parallel-twin, liquid cooled **Engine**

999cc Displacement

76.7 lb-ft @ 7,000 rpm Maximum Torque

Bore x Stroke 92.0 x 75.1mm

Compression Ratio 11.5:1

DFI® with two 50mm throttle bodies **Fuel System**

Ignition TCBI with Electronic Advance

Starting System Electric

Automatic CVT with centrifugal clutch (H,L,N,R) **Transmission**

Final Drive Selectable 2WD/4WD with locking front differential, shaft

Engine Braking Yes

Lighting **DETAILS**

Ladder type, tubular steel **Frame**

Overall Length 157.3 in **Overall Width** 68.1 in **Overall Height** 79.3 in

Curb Weight 2,163.1 lb* / 2,165.3 lb* CA Model

Wheelbase 125.8 in

Instruments Multi-function digital meter with bar-style tachometer (2 display options), digital speedometer, bar-style fuel gauge,

(2) LED headlights, (2) LED taillights, LED stoplight

gear indicator (L, H, N, R), Power Mode, driving mode (2WD/4WD/4WD+Diff Lock) indicator, Economical Riding Indicator, clock, odometer, dual trip meters, hour meter, water temperature, digital battery gauge, bar-style CTV temperature, seatbelt warning lamp, oil warning lamp, engine check lamp, water temperature warning lamp, neutral indicator lamp, reverse indicator lamp, parking indicator lamp, EPS warning

lamp, and CVT belt warning lamp.

Wheel Type Alloy wheels

Additional Features Roof, WARN® VRX 45 Winch

Color Choices Lime Green/Metallic Onyx Black, Sunbeam Red/Metallic Onyx

Black

6 Month Limited Warranty Warranty

Kawasaki Protection 12, 24, or 36 months Plus™ (optional)

CAPABILITY

Front Suspension / **Wheel Travel**

Double wishbone, FOX 2.5 LSC Piggyback Shocks, dual-rate coil-over springs, fully adjustable preload, and 24-way

adjustable compression damping/18.6 in

Rear Suspension / Wheel Travel

4-link trailing-arm rear suspension, FOX 2.5 LSC Piggyback Shocks, dual-rate coil-over springs, fully adjustable preload, and 24-way adjustable compression damping/21.1 in

Front Tires Maxxis® Carnivore 31 x 10.00R15 8PR

Rear Tires Maxxis® Carnivore 31 x 10.00R15 8PR

Electric Power Steering (EPS) / rack-and-pinion **Steering**

Front Brakes Dual hydraulic discs with two-piston calipers

Rear Brakes Dual hydraulic discs with single-piston calipers

Ground Clearance 14.4 in (max), 13.6 in (std)

Fuel Capacity 10.6 gal **Turning Radius** 23.3 ft

Scan with camera to view videos. key features

and more.

