VERSYS® 650 LT





MSRP **\$10,099**



METALLIC SPARK BLACK/METALLIC FLAT SPARK BLACK



P	N	V	V	F	R

Engine 4-stroke, 2-cylinder, DOHC, 8 valves, liquid-cooled

Displacement 649cc

Bore x Stroke 83.0 x 60.0mm

Compression

Ratio

10.8:1

Maximum Torque 47.0 lb-ft

Fuel System DFI® with 38mm Keihin throttle bodies (2)

Ignition TCBI with Electronic Advance

Transmission 6-speed with positive neutral finder

Final Drive Sealed chain

Electronic Rider Anti-lock Brake System (ABS), Kawasaki TRaction

Control (KTRC), Economical Riding Indicator

PERFORMANCE

Front Suspension / Wheel Travel 41mm telescopic fork with stepless adjustable rebound and spring preload/5.9 in

Rear Suspension Single offset laydown shock with remote

/ Wheel Travel adjustable spring preload/5.7 in

Front Tire 120/70 ZR-17

Rear Tire 160/60 ZR-17

Front Brakes Dual 300mm petal-style discs with 2-piston

calipers, ABS

Rear Brakes

Single 250mm petal-style disc with single-piston caliper, ABS

DETAILS

Frame Type Double pipe diamond frame constructed from

high-tensile steel

Rake/Trail 25°/4.3 in

Overall Length 85.2 in

Overall Width 33.1 in

Overall Height 53.5 in/55.9 in (windshield down/up)

Ground Clearance 6.7 in

Seat Height 33.3 in

Curb Weight 482.9 lb* (+ approx. 20 lb* w/ saddlebags & hand

guards)

Fuel Capacity 5.5 gal

Wheelbase 55.7 in

Special Features TFT color instrumentation with Smartphone

Connectivity via RIDEOLOGY THE APP, Cleanmount hard saddlebag system, featuring KQR™

mounts

Color Choices

Protection Plus™

Kawasaki

(optional)

Metallic Spark Black/Metallic Flat Spark Black

Warranty 24 Month Limited Warranty

12, 24, 36 or 48 months



