## 2023 **VULCAN<sup>®</sup> S**





MSRP NON-ABS \$7,349





**Front Tire** 

PEARL MATTE SAGE GREEN/METALLIC FLAT SPARK BLACK



METALLIC FLAT SPARK BLACK



120/70x18

## POWER

		Rear Tire	160/60x17
Engine	4-stroke, 2-cylinder, DOHC, liquid-cooled	Front Brakes	Single 300mm disc with twin-piston caliper
Displacement	649cc		(and ABS)
Bore x Stroke	83.0 x 60.0mm	Rear Brakes	Single 250mm disc with single-piston caliper (and ABS)
Compression Ratio	10.8:1	DETAILO	
Maximum	46.3 lb-ft @ 6,600 rpm	DETAILS	
Torque		Frame Type	High-tensile steel diamond frame
Fuel System	DFI® with 38mm throttle bodies (2), with sub- throttle valves	Rake/Trail	31°/4.7 in
Ignition	TCBI with Electronic Advance	<b>Overall Length</b>	90.9 in
Transmission	6-speed with positive neutral finder	Overall Width	34.6 in
Final Drive	Sealed chain	Overall Height	43.3 in
Electronic Rider Aids	Economical Riding Indicator, Anti-lock Brake System (ABS)	Ground Clearance	5.1 in
		Seat Height	27.8 in
PERFORMANCE		Curb Weight	498.3 lb* (ABS), 491.7 lb* (non-ABS)

## PERFURMANCE

Front Suspension / Wheel Travel

41mm telescopic fork/5.1 in

Rear Suspension / Wheel Travel

Scan with camera

to view videos,

key features

and more.

**Color Choices** Lay-down offset rear shock with linkage and adjustable preload/3.2 in

\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). When

3.7 gal

62.0 in

Black

Pearl Matte Sage Green/Metallic Flat Spark

equipped, California evaporative emissions equipment adds approximately 2.2 lb.

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A.

**Fuel Capacity** 

Wheelbase

Specifications subject to change. Visit Kawasaki.com for full product details.