²⁰²⁴ JET SKI[®] SX-R[™] 160







3-blade, oval-edge stainless steel

POWER

Engine	4-stroke, DOHC, four valves per cylinder, 4-cylinder inline	PE
Displacement	1,498cc	Lub
Bore x Stroke	83.0 x 69.2mm	Cou
Compression	10.6:1	Oil
Ratio		Fue
Induction	Naturally aspirated	Stor
Maximum	N/A	Сар
Boost Cooling System	Inducted water	DE
		Ove
Fuel System	DFI® with 60mm throttle body	Ove
Ignition	TCBI with Digital Advance	Ove
Starting System	Electric	Curl
		-
Propulsion System	148mm jet pump, axial-flow, single stage	Sea Cap

PERFORMANCE

Impeller

^{MSRP} **\$11,999**

EBONY/ICE GRAY

Lubrication	Semi-dry sump system
Coupling	Direct drive from engine
Oil Capacity	5.3 qt
Fuel Capacity	6.1 gal
Storage Capacity	N/A

DETAILS

	Overall Length	104.5 in
	Overall Width	30.1 in
	Overall Height	33.1 in
	Curb Weight	551.3 lb*
è	Seating Capacity	1
	Color Choices	Ebony/Ice Gray

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Ride responsibly. Kawasaki believes safety begins with us and continues with you. Always wear a USCG-approved personal flotation device, eyewear, gloves, footwear, and a wet suit or clothing that provides equivalent protection (board shorts with neoprene liner). Never ride under the influence of drugs or alcohol. Respect the rights of shoreline residents and other marine recreationists. Boat smart from the start. Take a Boating Safety course; for more information visit www.USCGBoating.org. Jet Ski watercraft are inboard powerboats and their use is subject to all applicable federal, state, and local boating laws. Read Owner's Manual and all on-product warnings. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit Kawasaki.com for full product details.