
2024 JET SKI[®] ULTRA[®] 310LX-S













Impeller

3-blade, oval-edge stainless steel

POWER

Engine	Supercharged and intercooled, 4-stroke, DOHC, four valves per cylinder, inline 4-	
	cylinder	l
Displacement	1,498cc	(
Bore x Stroke	83.0 x 69.2mm	0
Compression Ratio	8.2:1	F
Induction	Eaton Twin Vortices Series Roots-type	l
	supercharger with air-to-water intercooler	9
Maximum	16.8 psi	
Boost		
Cooling	Inducted water	
System		(
Fuel System	DFI® with 60mm throttle body	(
Ignition	TCBI with Digital Advance	(
Starting	Electric	
System		(
Propulsion	160mm jet pump, axial-flow, single stage	9
System		

PERFORMANCE

Lubrication	Semi-dry sump system
Coupling	Direct drive from engine
Oil Capacity	5.3 qt
Fuel Capacity	21.1 gal
Load Capacity	496 lb
Storage Capacity	44.5 gal

DETAILS

Overall Length 140.9 in	
Or could with (7.0 in	
Overall Width 47.0 in	
Overall Height 46.5 in	
Curb Weight 1,065.0 lb*	
Seating 3 Capacity	
Color Choices Ebony/Lime Green	

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Ride responsibly. Kawasaki believes safety begins with us and continues with you. Always wear a USCG-approved personal flotation device, eyewear, gloves, footwear, and a wet suit or clothing that provides equivalent protection (board shorts with neoprene liner). Never ride under the influence of drugs or alcohol. Respect the rights of shoreline residents and other marine recreationists. Boat smart from the start. Take a Boating Safety course; for more information visit www.USCGBoating.org. Jet Ski watercraft are inboard powerboats and their use is subject to all applicable federal, state, and local boating laws. Read Owner's Manual and all on-product warnings. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit Kawasaki.com for full product details.