## 2024 **KLR**<sup>®</sup>650 S





**MSRP NON-ABS** \$6,899





PEARL CRYSTAL WHITE/METALLIC CARBON GRAY



FIRECRACKER RED/METALLIC CARBON GRAY



POWER		Front Tire	90/90-21	
Engine	4-Stroke, single cylinder, DOHC	Rear Tire Front Brakes	130/80-17 Single 300mm disc with 2-piston calipers (and	
Displacement Bore x Stroke	652cc 100.0 x 83.0mm	Rear Brakes	ABS) Single 240mm disc with single-piston caliper (and ABS)	
Compression Ratio Maximum	Ratio		DETAILS	
Torque Fuel System	DFI® with 40mm throttle body	Frame Type Rake/Trail	Tubular, semi-double cradle	
Ignition	CDI	Overall Length	88.8 in	
Transmission	5-speed, return shift with wet multi-disc manual clutch	Overall Width Overall Height	38.2 in 56.3/54.9 in (screen hi/lo)	
Final Drive Electronic Rider	Sealed chain Anti-lock Brake System (ABS)	Ground	7.3 in	
Aids	And fock brake System (ADS)	Clearance Seat Height	32.1 in	
PERFORMANCE		Curb Weight	460.6 lb* (ABS), 456.2 lb* (non-ABS)	

Front Suspension / Wheel Travel 41mm telescopic fork/ 6.7 in

Rear Suspension / Wheel Travel Uni-Trak<sup>®</sup> single shock with adjustable rebound damping and adjustable spring preload/7.0 in

**Color Choices** Pearl Crystal White/Metallic Carbon Gray, Firecracker Red/Metallic Carbon Gray

6.1 gal

59.6 in

Scan with camera to view videos, key features and more.



\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). When equipped, California evaporative emissions equipment adds approximately 2.2 lb.

**Fuel Capacity** 

Wheelbase

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit Kawasaki.com for full product details.