
## <sup>2024</sup> KLX®110R L







## **POWER**

Engine	4-stroke single, SOHC, air-cooled	
Displacement	112cc	
Bore x Stroke	53.0 x 50.6mm	
Compression Ratio	9.5:1	
Fuel System	18mm Keihin carburetor and screw type throttle limiter on grip housing	
Ignition	DC-CDI	
Transmission	4-speed, return shift, wet multi-disc manual clutch	
Final Drive	Chain	

## PERFORMANCE

Front Suspension / Wheel Travel 30mm hydraulic telescopic fork/5.5 in

Rear Suspension / Wheel Travel Swingarm with single hydraulic shock/5.2 in

Front Tire	2.50 x 14
Rear Tire	3.00 x 12
Front Brakes	90mm mechanical drum, cable actuated
<b>Rear Brakes</b>	110mm mechanical drum, rod actuated

## DETAILS

ew type	Frame Type	Backbone frame, high-tensile steel
	Rake/Trail	24.2°/1.9 in
disc	Overall Length	61.4 in
	Overall Width	25.6 in
	Overall Height	39.0 in
	Ground Clearance	10.4 in
5.5 in	Seat Height	28.7 in
	Curb Weight	167.5 lb*
	Fuel Capacity	1.0 gal
	Wheelbase	42.3 in
	Color Choices	Lime Green, Battle Gray

Scan with camera to view videos, key features and more.



\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit Kawasaki.com for full product details.