


2024 KLX[®] 230 S

Kawasaki
Let the Good Times Roll[®]



MSRP NON-ABS
\$4,999

MSRP ABS
\$5,299



POWER

Engine	4-stroke single, SOHC, air-cooled
Displacement	233cc
Bore x Stroke	67.0 x 66.0mm
Compression Ratio	9.4:1
Maximum Torque	13.2 lb-ft @ 6,400 rpm
Fuel System	DFI [®] with 32mm throttle body
Ignition	TCBI with Electronic Advance
Transmission	6-speed
Final Drive	Sealed chain
Electronic Rider Aids	Anti-lock Brake System (ABS)

Rear Tire	4.10 x 18
Front Brakes	Single 240mm (265mm ABS Model) petal disc with a dual-piston caliper (and ABS)
Rear Brakes	Single 220mm petal disc with single-piston caliper (and ABS)

PERFORMANCE

Front Suspension / Wheel Travel	37mm telescopic fork/7.8 in
Rear Suspension / Wheel Travel	Uni-Trak [®] linkage system and single shock with adjustable spring preload/8.7 in
Front Tire	2.75 x 21

DETAILS

Frame Type	Perimeter, high-tensile steel
Rake/Trail	24.6° /3.7 in
Overall Length	81.8 in
Overall Width	33.2 in
Overall Height	44.8 in
Ground Clearance	9.4 in
Seat Height	33.3 in
Curb Weight	291.0/293.2 lb* 50-State Model
Fuel Capacity	2.0 gal
Wheelbase	53.7 in
Special Features	ERGO-FIT [®] , LCD Instrumentation with Smartphone Connectivity via RIDELOGY THE APP MOTORCYCLE
Color Choices	Lime Green, Battle Gray

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). When equipped, California evaporative emissions equipment adds approximately 2.2 lb. KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2024 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit Kawasaki.com for full product details.