
²⁰²⁴ KLX®300R







Rear Tire 4.6 x 18 POWER **Front Brakes** Single 270mm petal disc with a dualpiston caliper Engine 4-stroke single, DOHC, liquid-cooled **Rear Brakes** Single 240mm petal disc with single-Displacement 292cc piston caliper **Bore x Stroke** 78.0 x 61.2mm **DETAILS** Compression 11.1:1 Ratio **Frame Type** Semi-Double Cradle DFI[®] with 34mm Keihin throttle body **Fuel System** 26.9°/4.3 in Rake/Trail Ignition TCBI Electronic Advance **Overall Length** 86.6 in Transmission 6-speed, return shift with wet multi-disc manual clutch **Overall Width** 32.5 in Chain **Final Drive Overall Height** 49.0 in 11.8 in Ground PERFORMANCE Clearance Seat Height 35.4 in 43mm inverted telescopic fork with Front Suspension / adjustable compression damping /11.2 in **Curb Weight** 282.2 lb* / 286.7 lb* CA Model Wheel Travel **Fuel Capacity** 2.1 gal Uni-Trak[®] gas charged shock with Rear piggyback reservoir with adjustable Suspension / Wheelbase 56.5 in Wheel Travel compression, rebound damping and spring preload/11.2 in **Color Choices** Lime Green, Battle Gray **Front Tire** 3.0 x 21

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit Kawasaki.com for full product details.