MULE PRO-FX™ 1000 HD EDITION





\$16,799



FIRECRACKER RED



POWER

Engine 4-stroke, 2-cylinder, DOHC, liquid-cooled, gas

Displacement 999cc

Maximum Torque 61.5 lb-ft

Bore x Stroke 92.0 x 75.1mm

Compression Ratio 10.1:1

DFI® with 38mm throttle body **Fuel System**

Transmission Continuously Variable Transmission (CVT) with (L,H,N,R)

Final Drive Selectable 2WD/4WD, shaft Dual mode rear differential

with differential lock

Engine Braking Yes

Alternator Output

(max)

90 amp

Ground Clearance 11.9 in (max), 11.8 in (std)

Fuel Capacity 7.9 gal

Turning Radius 16.0 ft

Cargo Bed

54.1 x 53.3 x 11.0 in **Dimensions (LxWxH)**

Cargo Bed Load

Capacity

999 lb / 600.0 lb CA Model

Payload Capacity 1,616.3 lb / 1,263.5 lb CA Model

Seating Capacity

Towing Capacity 2.000 lb

(2) Halogen headlights. (2) LED headlights Lighting

CAPABILITY

Double wishbone/11.0 in Front Suspension / **Wheel Travel**

Rear Suspension /

Double wishbone/10.1 in

Wheel Travel

26 x 9.00-12, radial

Rear Tires

Front Tires

26 x 11.00-12, radial

Steering

Rack-and-pinion

Front Brakes

Dual Disc, 2 piston caliper

Rear Brakes

Dual Disc, 1 piston caliper

Park Brake Type

Independent, Mechanical Disc

DETAILS

Overall Length 136.6 in

Overall Width 64.0 in

Overall Height 81.1 in

Curb Weight 1,891.9 lb* / 1,894.1 lb* CA Model

Wheelbase 92.3 in

Instruments

Multi-function display includes digital speedometer, fuel gauge, odometer, hour meter, clock, dual trip meters,

2WD/4WD indicator, water temperature warning indicator, oil pressure warning indicator, fuel injection warning indicator, CVT warning indicator, neutral, reverse and

parking indicators, seatbelt reminder lamps

Wheel Type Steel

Additional Features

Roof, Rear Bumper, Additional Under Seat Storage Bin, Rearview Mirror, Hydraulic Cargo Bed Lift, Self-Leveling

Rear Suspension, Anti-cinch Seatbelts

Color Choices Firecracker Red

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). All MULE™ PRO Series side x side's Rollover Protective Structure (ROPS) meets the performance requirements of ISO 3471