2024 **MULE PRO-FXR[™] 1000**





POWER

| Engine | 4-stroke, 2-cylinder, DOHC, liquid-cooled, gas |
|----------------------------|--|
| Displacement | 999cc |
| Maximum Torque | 61.5 lb-ft |
| Bore x Stroke | 92.0 x 75.1mm |
| Compression Ratio | 10.1:1 |
| Fuel System | DFI® with 38mm throttle body |
| Transmission | Continuously Variable Transmission (CVT) with (L,H,N,R) |
| Final Drive | Selectable 2WD/4WD, shaft Dual mode rear differential with differential lock |
| Engine Braking | Yes |
| Alternator Output (max) | 90 amp |

| oround clearance | 13.2 m (max), 12.2 m (3td) |
|---------------------------------|--|
| Fuel Capacity | 7.9 gal |
| Turning Radius | 14.0 ft |
| Cargo Bed Dimensions (LxWxH) | 37.6 x 53.3 x 11.0 in |
| Cargo Bed Load Capacity | 999 lb / 600.0 lb CA Model |
| Payload Capacity | 1,616.3 lb / 1,263.5 lb CA Model |
| Seating Capacity | 3 |
| Towing Capacity | 2,000 lb |
| Lighting | (2) Halogen headlights. (2) LED headlights |
| | |

13.2 in (max), 12.2 in (std)

DETAILS

Ground Clearance

| 90 amp | | |
|---|--|---|
| | Overall Length | 122.0 in |
| | Overall Width | 64.0 in |
| | Overall Height | 77.2 in |
| Double wishbone/11.0 in | Curb Weight | 1,735.3 lb* / 1,737.5 lb* CA Model |
| Double wishbone/10.1 in | Wheelbase | 79.7 in |
| 27 x 9.00-12, radial 27 x 11.00-12, radial Electric Power Steering (EPS), Tilt steering Dual Disc, 2 piston caliper Dual Disc, 1 piston caliper Independent, Mechanical Disc | Instruments Wheel Type Additional Features | Multi-function display includes digital speedometer, fuel gauge, odometer, hour meter, clock, dual trip meters, 2WD/4WD indicator, water temperature warning indicator, oil pressure warning indicator, fuel injection warning indicator, CVT and EPS warning indicators, neutral, reverse and parking indicators, seatbelt reminder lamps Alloy Rear Bumper, Contoured Two-Tone Bench Seat |
| | Color Choices | Metallic Sierra Blue |
| | | |

*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

All MULETM PRO Series side x side's Rollover Protective Structure (ROPS) meets the performance requirements of ISO 3471.

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear protective gear appropriate for the use of this vehicle. Never operate under the influence of drugs or alcohol. Protect the environment. The Kawasaki MULETM side x side is an off- highway vehicle only, and is not designed, equipped or manufactured for use on public streets, roads or highways. Obey the laws and regulations that control the use of your vehicle. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit Kawasaki.com for full product details.

CAPABILITY

Front Suspension / Wheel Travel

Rear Suspension / Wheel Travel **Front Tires**

Rear Tires

Steering

Front Brakes Rear Brakes

Park Brake Type

Scan with camera to view videos, key features and more.



Let the Good Times Roll