

2024

NINJA H2®R ABS


Kawasaki

Let the Good Times Roll®



MSRP

\$58,100

 MIRROR COATED MATTE SPARK BLACK



POWER		Rear Suspension / Wheel Travel	
Engine	Liquid-cooled, 4-stroke, In-Line Four, DOHC, 16-valve	Front Tire	Uni-Trak®, Öhlins TTX36 gas charged shock with piggyback reservoir, 30-way compression and rebound damping adjustability, 16-way spring preload adjustability, and top-out spring/5.3 in
Displacement	998cc	Rear Tire	120/60 ZR17 V01F slick
Bore x Stroke	76.0 x 55.0mm	Front Brakes	190/65 ZR17 V01R slick
Compression Ratio	8.3:1	Rear Brakes	Dual radial-mount, opposed 4-piston Brembo Stylema® calipers, dual semi-floating 330mm discs, Kawasaki Intelligent anti-lock Brake System (KIBS)
Maximum Torque	121.5 lb-ft @ 12,500 rpm		Opposed 2-piston calipers, single 250mm disc, Kawasaki Intelligent anti-lock Brake System (KIBS)
Fuel System	DFI® with 50mm throttle bodies (4) with dual injection; Kawasaki Supercharger	DETAILS	
Ignition	Digital	Frame Type	Trellis, high-tensile steel, with swingarm mounting plate
Transmission	6-speed, return, dog-ring	Rake/Trail	25.1° / 4.3 in
Final Drive	Sealed chain	Overall Length	81.5 in
Electronic Rider Aids	Kawasaki Cornering Management Function (KCMF), Kawasaki TRaction Control (KTRC), Kawasaki Launch Control Mode (KLCM), Kawasaki Intelligent anti-lock Brake System (KIBS), Kawasaki Engine Brake Control (KEBC), Kawasaki Quick Shifter (KQS) (upshift & downshift), Öhlins Electronic Steering Damper	Overall Width	33.5 in
PERFORMANCE		Overall Height	45.7 in
Front Suspension / Wheel Travel	43mm inverted fork with adjustable rebound and compression damping, spring preload adjustability and top-out springs/4.7 in	Ground Clearance	5.1 in
		Seat Height	32.7 in
		Curb Weight	476.3 lb*
		Fuel Capacity	4.5 gal
		Wheelbase	57.1 in
		Special Features	Aerodynamic downforce generating devices, Highly Durable Paint, Analog Tach & LCD instrumentation
		Color Choices	Mirror Coated Matte Spark Black

Scan with camera
to view videos,
key features
and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). When equipped, California evaporative emissions equipment adds approximately 2.2 lb.
KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A.
Specifications subject to change. Visit Kawasaki.com for full product details.