


2024

NINJA H2[®]R ABS

Kawasaki
Let the Good Times Roll[®]



MSRP
\$58,100

 MIRROR COATED MATTE SPARK BLACK



POWER

Engine	Liquid-cooled, 4-stroke, In-Line Four, DOHC, 16-valve
Displacement	998cc
Bore x Stroke	76.0 x 55.0mm
Compression Ratio	8.3:1
Maximum Torque	121.5 lb-ft @ 12,500 rpm
Fuel System	DFI [®] with 50mm throttle bodies (4) with dual injection; Kawasaki Supercharger
Ignition	Digital
Transmission	6-speed, return, dog-ring
Final Drive	Sealed chain
Electronic Rider Aids	Kawasaki Cornering Management Function (KCMF), Kawasaki Traction Control (KTRC), Kawasaki Launch Control Mode (KLCM), Kawasaki Intelligent anti-lock Brake System (KIBS), Kawasaki Engine Brake Control (KEBC), Kawasaki Quick Shifter (KQS) (upshift & downshift), Öhlins Electronic Steering Damper

Rear Suspension / Wheel Travel	Uni-Trak [®] , Öhlins TTX36 gas charged shock with piggyback reservoir, 30-way compression and rebound damping adjustability, 16-way spring preload adjustability, and top-out spring/5.3 in
Front Tire	120/60 ZR17 V01F slick
Rear Tire	190/65 ZR17 V01R slick
Front Brakes	Dual radial-mount, opposed 4-piston Brembo Stylema [®] calipers, dual semi-floating 330mm discs, Kawasaki Intelligent anti-lock Brake System (KIBS)
Rear Brakes	Opposed 2-piston calipers, single 250mm disc, Kawasaki Intelligent anti-lock Brake System (KIBS)

PERFORMANCE

Front Suspension / Wheel Travel	43mm inverted fork with adjustable rebound and compression damping, spring preload adjustability and top-out springs/4.7 in
--	---

DETAILS

Frame Type	Trellis, high-tensile steel, with swingarm mounting plate
Rake/Trail	25.1° / 4.3 in
Overall Length	81.5 in
Overall Width	33.5 in
Overall Height	45.7 in
Ground Clearance	5.1 in
Seat Height	32.7 in
Curb Weight	476.3 lb*
Fuel Capacity	4.5 gal
Wheelbase	57.1 in
Special Features	Aerodynamic downforce generating devices, Highly Durable Paint, Analog Tach & LCD instrumentation
Color Choices	Mirror Coated Matte Spark Black

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). When equipped, California evaporative emissions equipment adds approximately 2.2 lb. KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2024 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit Kawasaki.com for full product details.