RIDGE® HVAC





\$27,999



CANDY PERSIMMON RED



POWER

Engine 4-stroke, DOHC, 4-valve In-Line Four-Cylinder, liquid-cooled

999cc **Displacement**

Maximum Horsepower 92.0 hp1 @ 8,500 rpm **Maximum Torque** 65.8 lb-ft @ 5,500 rpm

Bore x Stroke 73.4 x 59.0mm

Compression Ratio 10.6:1 **Fuel System** EFI

Ignition TCBI with Digital Advance

Starting System Electric

Continuously Variable Transmission (CVT) with (H,L,N,R) **Transmission Final Drive** Selectable 4WD with locking rear differential, shaft

Engine Braking Yes

Alternator Output

(max)

85 amp

Electronic Rider Aids Power Modes, Economical Riding Indicator **Ground Clearance** 12.6/13.6 in (max preload); 12.6 in CA Model

Fuel Capacity 12.9 gal **Turning Radius** 15.0 ft

Cargo Bed Dimensions 34.6 x 49.0 x 12.8 in

(LxWxH)

1,000/600 lb CA Model

Cargo Bed Load Capacity **Payload Capacity**

1,499/1,100 lb CA Model

Seating Capacity 3. bench seat **Towing Capacity** 2,500 lbs

All-LED lighting

DETAILS

Lighting

Frame Ladder type, tubular steel

Overall Length 124.4 in **Overall Width** 64.0 in **Overall Height** 81.3 in

1,938.2/1,940.5 lb** CA Model **Dry Weight Curb Weight** 2,044.0/2,046.2 lb* CA Model

Wheelbase 90.7 in

Instruments

Digital speedometer, tachometer, fuel gauge, odometer, dual trip meters, total time, trip time, average speed, gear indicator,

Driving Mode, Power Mode, clock, water temperature, battery voltage, oil change reminder, Bluetooth indicator, Economical Riding Indicator, maintenance reminder, high beam, neutral, reverse, and warning lights (battery, EPS, CVT, seatbelt, parking

indicator, oil pressure, water temperature)

Additional Features

Color Choices

Full Cab with HVAC, Adjustable driver's seat, ERGO-FIT®, Fullcolor TFT Instrumentation with Smartphone Connectivity via RIDEOLOGY THE APP Powersports, USB ports, KQR™ system

compatible

Candy Persimmon Red

CAPABILITY

Front Suspension / Wheel Travel

Long-Travel, Double Wishbone/12.7 in

Long-Travel, Double Wishbone/12.7 in

Rear Suspension / **Wheel Travel**

Duro 27 x 9-14

Front Tires Rear Tires

Duro 27 x 11-14

Wheel Type

14" Aluminum

Steering

Rack-and-pinion w/ Electric Power Steering (EPS)

Front Brakes

Dual hydraulic 249mm discs with two-piston calipers

Rear Brakes

Dual hydraulic 249mm discs with single-piston calipers

Scan with camera to view videos, key features and more.



Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). **Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). ¹This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard. Specifications subject to change. Visit Kawasaki.com for full product details.