2024 **RIDGE® RANCH EDITION**





METALLIC STARDUST WHITE



Let the Good Times Roll

POWER

Engine	4-stroke, DOHC, 4-valve In-Line Four-Cylinder, liquid-cooled
Displacement	999cc
Maximum Horsepower	92.0 hp ¹ @ 8,500 rpm
Maximum Torque	65.8 lb-ft @ 5,500 rpm
Bore x Stroke	73.4 x 59.0mm
Compression Ratio	10.6:1
Fuel System	EFI
Ignition	TCBI with Digital Advance
Starting System	Electric
Transmission	Continuously Variable Transmission (CVT) with (H,L,N,R)
Final Drive	Selectable 4WD with locking rear differential, shaft
Engine Braking	Yes
Alternator Output (max)	85 amp
Electronic Rider Aids	Power Modes, Economical Riding Indicator

CAPABILITY

Front Suspension / Wheel Travel	Long-Travel, Double Wishbone/12.7 in	Wheelbase	90.7 in
Rear Suspension / Wheel Travel	Long-Travel, Double Wishbone/12.7 in	Instruments	Digital speedometer, tachometer, fuel gauge, odometer, dual trip meters, total time, trip time, average speed, gear indicator, Driving Mode, Power Mode, clock, water temperature, battery voltage, oil change reminder, Bluetooth indicator, Economical
Front Tires	Duro 27 x 9-14		Riding Indicator, maintenance reminder, high beam, neutral, reverse, and warning lights (battery, EPS, CVT, seatbelt, parking
Rear Tires	Duro 27 x 11-14		indicator, oil pressure, water temperature)
Wheel Type	14" Aluminum	Additional Features	WARN® VRX 45 Powersport Winch, Adjustable driver's seat,
Steering	Rack-and-pinion w/ Electric Power Steering (EPS)	ectric Power Steering (EPS) ERGO-FIT®, Full-color TFT Instrum Connectivity via RIDEOLOGY THE /	
Front Brakes	Dual hydraulic 249mm discs with two-piston calipers		KQR™ system compatible
Rear Brakes	Dual hydraulic 249mm discs with single-piston calipers	Color Choices	Metallic Stardust White





*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). **Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard. Specifications subject to change. Visit Kawasaki.com for full product details.

Ground Clearance	12.6/13.6 in (max preload); 12.6 in CA Model
Fuel Capacity	12.9 gal
Turning Radius	15.0 ft
Cargo Bed Dimensions (LxWxH)	34.6 x 49.0 x 12.8 in
Cargo Bed Load Capacity	1,000/600 lb CA Model
Payload Capacity	1,499/1,100 lb CA Model
Seating Capacity	3, bench seat
Towing Capacity	2,500 lbs
Lighting	All-LED lighting

Ladder type, tubular steel

1,808.1/1,810.3 lb** CA Model

1,909.5/1,911.7 lb* CA Model

126.4 in

64.0 in

81.9 in

DETAILS

Overall Length

Overall Width

Overall Height

Dry Weight

Curb Weight

Frame