RIDGE® XR HVAC





\$29,999



ICE GRAY



METALLIC GRAYSTONE



12.9 gal

15.0 ft

34.6 x 49.0 x 12.8 in

1,000/600 lb CA Model

1,499/1,100 lb CA Model

2. bucket seat

All-LED lighting

2,500 lbs

13.8/14.6 in (max preload); 13.8 in CA Model

POWER

4-stroke, DOHC, 4-valve In-Line Four-Cylinder, liquid-cooled **Engine**

999cc **Displacement**

Maximum Horsepower 116.0 hp1 @ 8,500 rpm **Maximum Torque** 73.8 lb-ft @ 8,000 rpm

Bore x Stroke 73.4 x 59.0mm

Compression Ratio 10.6:1 **Fuel System** EFI

Ignition TCBI with Digital Advance

Starting System Electric

Continuously Variable Transmission (CVT) with (H,L,N,R) **Transmission Final Drive** Selectable 4WD with locking front/rear differential, shaft

Engine Braking

Alternator Output (max)

Electronic Rider Aids

CAPABILITY

Front Suspension /

Rear Suspension /

85 amp

Duro 30 x 10-14

Duro 30 x 10-14

14" Aluminum

Power Modes, Economical Riding Indicator

Long-Travel, Double Wishbone/12.7 in

Long-Travel, Double Wishbone/12.7 in

Rack-and-pinion w/ Electric Power Steering (EPS)

Dual hydraulic 249mm discs with two-piston calipers

DETAILS

Lighting

Ground Clearance

Fuel Capacity

Turning Radius

Cargo Bed Load

Payload Capacity

Seating Capacity

Towing Capacity

(LxWxH)

Capacity

Cargo Bed Dimensions

Frame Ladder type, tubular steel

Overall Length 125.4 in **Overall Width** 64.0 in **Overall Height** 82.3 in

1,960.3/1,962.5 lb** CA Model **Dry Weight Curb Weight** 2,066.1/2,068.3 lb* CA Model

Wheelbase 90.7 in

Instruments

Digital speedometer, tachometer, fuel gauge, odometer, dual trip meters, total time, trip time, average speed, gear indicator, Driving Mode, Power Mode, clock, water temperature, battery voltage, oil change reminder, Bluetooth indicator, Economical Riding Indicator, maintenance reminder, high beam, neutral, reverse, and warning lights (battery, EPS, CVT, seatbelt, parking

indicator, oil pressure, water temperature)

Additional Features

Full Cab with HVAC, Adjustable driver/passenger seats, ERGO-FIT®, Full-color TFT Instrumentation with Smartphone Connectivity via RIDEOLOGY THE APP Powersports, USB ports,

KQR™ system compatible

Wheel Travel

Wheel Travel

Front Tires

Rear Tires

Wheel Type

Steering

Rear Brakes

Front Brakes

Scan with camera

to view videos,

key features

and more.

Color Choices Ice Gray, Metallic Graystone Dual hydraulic 249mm discs with single-piston calipers Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). **Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). ¹This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of

Specifications subject to change. Visit Kawasaki.com for full product details.

many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard.