

2024

# Z650RS ABS

MSRP  
**\$9,599**

 EBONY/METALLIC MATTE CARBON GRAY



POWER		Rear Tire	
Engine	4-stroke, 2-cylinder, DOHC, liquid-cooled	Front Brakes	160/60 ZR17
Displacement	649cc	Rear Brakes	Dual 300mm petal-style discs with two-piston calipers, (and ABS)
Bore x Stroke	83.0 x 60.0mm		Single 220mm petal-style disc, (and ABS)
Compression Ratio	10.8:1	DETAILS	
Maximum Torque	48.5 lb-ft @ 6,500 rpm	Frame Type	Trellis, high tensile steel
Fuel System	DFI® with Keihin 36mm throttle bodies	Rake/Trail	24.0° / 3.9 in
Ignition	TCBI with Electronic Advance	Overall Length	81.3 in
Transmission	6-speed, return shift	Overall Width	31.5 in
Final Drive	Sealed chain	Overall Height	43.9 in
Electronic Rider Aids	Economical Riding Indicator, Kawasaki TRaction Control (KTRC - 3 Modes), Anti-lock Brake System (ABS)	Ground Clearance	4.9 in
PERFORMANCE		Seat Height	31.5 in
Front Suspension / Wheel Travel	Telescopic fork/4.9 in	Curb Weight	412.3 lb*
Rear Suspension / Wheel Travel	Horizontal back-link with adjustable preload, swingarm/5.1 in	Fuel Capacity	3.2 gal
Front Tire	120/70 ZR17	Wheelbase	55.3 in
		Color Choices	Ebony/Metallic Matte Carbon Gray
		Warranty	12 Month Limited Warranty
		Kawasaki Protection Plus™ (optional)	12, 24, 36, or 48 months

Scan with camera  
to view videos,  
key features  
and more.



\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). When equipped, California evaporative emissions equipment adds approximately 2.2 lb.  
KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2024 Kawasaki Motors Corp., U.S.A.  
Specifications subject to change. Visit [Kawasaki.com](https://www.kawasaki.com) for full product details.