2025 **VULCAN® 900 CUSTOM**





Let the Good Times Roll

POWER

Engine	4-stroke, 55-degree V-twin, liquid-cooled
Displacement	903cc
Bore x Stroke	88.0 x 74.2mm
Compression Ratio	9.5:1
Maximum Torque	58.2 lb-ft @ 3,500 rpm
Fuel System	DFI® with 34mm throttle bodies (2), with sub-throttle valves
Ignition	TCBI with Electronic Advance
Transmission	5-speed with positive neutral finder
Final Drive	Kevlar-reinforced belt

Front Tire 80/90-21 **Rear Tire** 180/70-15 **Front Brakes** Single 300mm hydraulic disc Single 270mm hydraulic disc **Rear Brakes**

DETAILS

58.2 lb-ft @ 3,500 rpm	Frame Type	Semi-double cradle, high-tensile steel
	Rake/Trail	33°/7.2 in
DFI® with 34mm throttle bodies (2), with sub-throttle valves	Overall Length	94.7 in
TCBI with Electronic Advance	Overall Width	35.2 in
5-speed with positive neutral finder	Overall Height	44.1 in
Kevlar-reinforced belt	Ground Clearance	5.5 in
ANCE	Seat Height	27.0 in
	Curb Weight	610.8 lb*
41mm Showa telescopic fork/5.9 in	Fuel Capacity	5.3 gal
	Wheelbase	64.8 in
Uni-Trak® swingarm, 7-way adjustable spring preload/4.1 in	Color Choices	Candy Fire Red/Ebony

Suspension / Wheel Travel

Front

PERFORMANCE

Rear Suspension / Wheel Travel Uni-Trak spring p

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). When equipped, California evaporative emissions equipment adds approximately 2.2 lb.

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit Kawasaki.com for full product details.