## <sup>2025</sup> KLX<sup>®</sup>230R







## **Rear Tire** 100/100-18 **POWER** Single 240mm petal disc with a dual-**Front Brakes** piston caliper 4-stroke, single-cylinder, SOHC, air-Engine cooled **Rear Brakes** Single 220mm petal disc with singlepiston caliper Displacement 233cc 67.0 x 66.0mm **Bore x Stroke DETAILS** Compression 9.4:1 Ratio **Frame Type** High-tensile steel, box-section perimeter DFI® with 32mm Keihin throttle body **Fuel System** Rake/Trail 25.4°/4.2 in TCBI with electronic advance Ignition **Overall Length** 80.5 in Transmission 6-speed, return shift with wet multi-disc **Overall Width** 33.3 in manual clutch **Overall Height** 47.2 in **Final Drive** Chain 11.4 in Ground Clearance

## PERFORMANCE

		Seal neight	33.0 111
Front Suspension /	37mm telescopic fork/9.8 in	Curb Weight	262.4 lb* / 264.5 lb* 50-State Model
Wheel Travel		Fuel Capacity	2.0 gal
Rear Suspension /	Uni-Trak® linkage system and single shock with adjustable spring preload/9.8	Wheelbase	54.1 in
Wheel Travel	in	<b>Color Choices</b>	Lime Green, Battle Gray
Front Tire	80/100-21		

Scan with camera to view videos, key features and more.



\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit Kawasaki.com for full product details.

at Unight

DE C in