²⁰²⁵ **KLX[®]230R S**







100/100-18

POWER

IONEN		Front Brakes	Single 240mm petal disc with a dual-	
Engine	4-stroke, single-cylinder, SOHC, air- cooled		piston caliper	
Displacement	233cc	Rear Brakes	Single 220mm petal disc with single- piston caliper	
Displacement	25500		hh.	
Bore x Stroke	67.0 x 66.0mm	DETAILS	DETAILS	
Compression	9.4:1			
Ratio		Frame Type	High-tensile steel, box-section perimeter	
Fuel System	DFI® with 32mm Keihin throttle body	Rake/Trail	24.6°/3.9 in	
Ignition	TCBI with electronic advance	Overall Length	80.5 in	
Transmission	6-speed, return shift with wet multi-disc manual clutch	Overall Width	33.3 in	
Final Drive	Chain	Overall Height	46.7 in	
		Ground	10.6 in	
		Clearance		

Rear Tire

PERFORMANCE

		Seat Height	34.4 IN	
	Front Suspension /	37mm telescopic fork/8.7 in	Curb Weight	262.4 lb* / 264.5 lb* 50-State Model
N	Wheel Travel		Fuel Capacity	2.0 gal
	Rear Suspension /	Uni-Trak® linkage system and single shock with adjustable spring preload/8.8	Wheelbase	53.3 in
Wheel T	Wheel Travel	vel in	Color Choices	Lime Green, Battle Gray
	Front Tire	80/100-21		





*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©?2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit Kawasaki.com for full product details.