
2025 **KLX®300**







POWER		Front Tire Rear Tire	3.0 x 21
Engine	4-stroke, single-cylinder, DOHC, liquid- cooled	Front Brakes	4.6 x 18 Single 250mm petal disc with a dual-piston caliper
Displacement	292cc	Rear Brakes	Single 240mm petal disc with single-piston
Bore x Stroke	78.0 x 61.2mm		caliper
Compression Ratio	11.1:1	DETAILS	
Maximum Torque	18.1 lb-ft @ 7,000 rpm	Frame Type	Tubular, semi-double cradle
Fuel System	DFI® with 34mm Keihin throttle body	Rake/Trail	26.7°/4.2 in
Ignition	CDI	Overall Length	86.6 in
Transmission	6-speed, return shift with wet multi-disc	Overall Width	32.3 in
	manual clutch	Overall Height	47.4 in
Final Drive	Chain	Ground Clearance	10.8 in
PERFORMANCE		Seat Height	35.2 in
Front	43mm inverted telescopic fork with	Curb Weight	302.1 lb*
Suspension / Wheel Travel	adjustable compression damping/10.0 in	Fuel Capacity	2.1 gal
Rear	Uni-Trak® gas charged shock with piggyback	Wheelbase	56.7 in

Suspension / Wheel Travel reservoir with adjustable compression, rebound damping and spring preload/9.1 in

Lime Green, Battle Gray



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit Kawasaki.com for full product details.

Color Choices