
²⁰²⁵ KLX®300SM







Rear Suspension Uni-Trak[®] gas charged shock with piggyback POWER / Wheel Travel reservoir with adjustable rebound damping and spring preload/8.1 in 4-stroke, single-cylinder, DOHC, liquid-cooled Engine **Front Tire** 110/70-17 Displacement 292cc **Rear Tire** 130/70-17 **Bore x Stroke** 78.0 x 61.2mm **Front Brakes** Single 300mm petal disc with a dual-piston caliper Compression 11.1:1 Ratio **Rear Brakes** Single 240mm petal disc with single-piston **Maximum Torque** 18.1 lb-ft @ 7,000 rpm caliper **Fuel System** DFI® with 34mm Keihin throttle body DETAILS Ignition CDI Transmission 6-speed, return shift with wet multi-disc manual clutch **Final Drive** Chain

PERFORMANCE

Front Suspension / Wheel Travel 43mm inverted cartridge fork with adjustable compression damping/9.1 in

Frame Type	Tubular, semi-double cradle
Rake/Trail	25.0°/2.8 in
Overall Length	83.3 in
Overall Width	31.1 in
Overall Height	44.7 in
Ground Clearance	9.3 in
Seat Height	33.9 in
Curb Weight	304.3 lb*
Fuel Capacity	2.1 gal
Wheelbase	56.5 in
Color Choices	Battle Gray, Phantom Blue





*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). When equipped, California evaporative emissions equipment adds approximately 2.2 lb.

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A.

Specifications subject to change. Visit Kawasaki.com for full product details.