²⁰²⁵ **KX**[™]65

Kawasaki Let the Good Times Roll®





Rear Tire 80/100-12 **POWER Front Brakes** Single 180mm disc with single-piston caliper Engine 2-stroke, single-cylinder, liquid-cooled Single 180mm disc with single-piston **Rear Brakes** Displacement 64cc caliper **Bore x Stroke** 44.5 x 41.6mm **DETAILS** Compression 8.4:1 Ratio High-tensile steel semi-double cradle Frame Type **Fuel System** 24mm Mikuni carburetor Rake/Trail 27.0°/2.4 in Ignition CDI with digital advance **Overall Length** 62.6 in Transmission 6-speed, return shift, with wet multi-disc manual clutch **Overall Width** 29.9 in **Final Drive** Chain **Overall Height** 37.6 in Ground 12.0 in PERFORMANCE Clearance **Seat Height** 29.9 in 33mm leading axle telescopic fork with Front Suspension / 4-way rebound damping/8.3 in **Curb Weight** 132.2 lb* Wheel Travel **Fuel Capacity** 1.0 gal Uni-Trak[®] single shock system with Rear Suspension / stepless 3-turns rebound damping and Wheelbase 44.1 in fully adjustable spring preload/9.4 in Wheel Travel

Front Tire

60/100-14

*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit Kawasaki.com for full product details.

Lime Green

Color Choices

Scan with camera to view videos, key features and more.

