2025 **MULE PRO-DX[™] EPS**





BRIGHT WHITE

10.4 in



POWER

Engine	4-stroke, 3-cylinder, OHV, liquid-cooled, diesel	
Displacement	993cc	
Maximum Torque	38.3 lb-ft @ 2,400 rpm	
Bore x Stroke	74.0 x 77.0mm	
Compression Ratio	23.5:1	
Fuel System	Bosch in-line injection pump	
Transmission	Continuously Variable Transmission (CVT) with (H,L,N,R)	
Final Drive	Selectable 2WD/4WD, shaft. Dual mode rear differential with differential lock	
Engine Braking	Yes	
Alternator Output	55 amp	

	Fuel Capacity	7.9 gal
	Turning Radius	16.0 ft
	Cargo Bed Dimensions (LxWxH)	54.1 x 53.7 x 11.0 in
	Cargo Bed Load Capacity	999 lb
	Payload Capacity	1,574 lb
	Seating Capacity	3-person
	Towing Capacity	2,000 lb
	Lighting	(2) Halogen headlights
÷		

DETAILS

Ground Clearance

Overall Length	133.3 in
Overall Width	64.0 in
Overall Height	77.4 in
Dry Weight	1,781.6 lb**
Curb Weight	1,858.8 lb*
Wheelbase	92.3 in
Instruments	Multi-function display includes digital speedometer, fuel gauge, odometer, hour meter, clock, dual trip meters, 2WD/4WD indicator, water temperature warning indicator, oil pressure warning indicator, glow plug indicator, CVT and EPS warning indicators, neutral, reverse and parking indicators, seatbelt reminder lamps
Color Choices	Bright White

(max)

CAPABILITY

Front Suspension / Wheel Travel	Double wishbone/8.7 in	
Rear Suspension / Wheel Travel	Double wishbone/8.5 in (L)/8.7 in (R)	
Front Tires	26 x 9-12	
Rear Tires	26 x 11-12	
Steering	Electric Power Steering (EPS), Tilt steering	
Front Brakes	Dual disc, 2-piston caliper	
Rear Brakes	Dual disc, 1-piston caliper	
Park Brake Type	Independent, mechanical disc	

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). **Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied) All MULETM PRO Series side x side's Rollover Protective Structure (ROPS) meets the performance requirements of ISO 3471.

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear protective gear appropriate for the use of this vehicle. Never operate under the influence of drugs or alcohol. Protect the environment. The Kawasaki MULETM side x side is an off- highway vehicle only, and is not designed, equipped or manufactured for use on public streets, roads or highways. Obey the laws and regulations that control the use of your vehicle. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit Kawasaki.com for full product details.