


2025

# MULE PRO-DXT™ EPS

**Kawasaki**  
Let the Good Times Roll®



MSRP  
**\$19,799**

 SUPER BLACK



## POWER

|                         |   |
|-------------------------|---|
| Engine                  | 4-stroke, 3-cylinder, OHV, liquid-cooled, diesel                              |
| Displacement            | 993cc   |
| Maximum Torque          | 38.3 lb-ft @ 2,400 rpm  |
| Bore x Stroke           | 74.0 x 77.0mm   |
| Compression Ratio       | 23.5:1  |
| Fuel System             | Bosch in-line injection pump  |
| Transmission            | Continuously Variable Transmission (CVT) with (H,L,N,R)                       |
| Final Drive             | Selectable 2WD/4WD, shaft. Dual mode rear differential with differential lock |
| Engine Braking          | Yes   |
| Alternator Output (max) | 55 amp  |

|                              |   |
|------------------------------|---|
| Ground Clearance             | 10.2 in   |
| Fuel Capacity                | 7.9 gal   |
| Turning Radius               | 16.0 ft   |
| Cargo Bed Dimensions (LxWxH) | 42.7 x 53.7 x 11.0 in (3-person) / 22.0 x 53.7 x 11.0 in (6-person) |
| Cargo Bed Load Capacity      | 999 lb (3-person) / 350 lb (6-person)                               |
| Payload Capacity             | 1,574 lb  |
| Seating Capacity             | 3-person (1-row), 6-person (2-row)                                  |
| Towing Capacity              | 2,000 lb  |
| Lighting                     | (2) Halogen headlights  |

## CAPABILITY

|                                 |  |
|---------------------------------|--|
| Front Suspension / Wheel Travel | Double wishbone/8.7 in                       |
| Rear Suspension / Wheel Travel  | Double wishbone/8.5 in (L)/8.7 in (R)        |
| Front Tires                     | 26 x 9-12                                    |
| Rear Tires                      | 26 x 11-12                                   |
| Steering                        | Electric Power Steering (EPS), Tilt steering |
| Front Brakes                    | Dual disc, 2-piston caliper                  |
| Rear Brakes                     | Dual disc, 1-piston caliper                  |
| Park Brake Type                 | Independent, mechanical disc                 |

## DETAILS

|                |   |
|----------------|---|
| Overall Length | 133.3 in  |
| Overall Width  | 64.0 in   |
| Overall Height | 77.6 in   |
| Curb Weight    | 1,942.6 lb*   |
| Wheelbase      | 92.3 in   |
| Instruments    | Multi-function display includes digital speedometer, fuel gauge, odometer, hour meter, clock, dual trip meters, 2WD/4WD indicator, water temperature warning indicator, oil pressure warning indicator, glow plug indicator, CVT and EPS warning indicators, neutral, reverse and parking indicators, seatbelt reminder lamps |
| Color Choices  | Super Black   |

Scan with camera to view videos, key features and more.



\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). All MULE™ PRO Series side x side's Rollover Protective Structure (ROPS) meets the performance requirements of ISO 3471. KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear protective gear appropriate for the use of this vehicle. Never operate under the influence of drugs or alcohol. Protect the environment. The Kawasaki MULE™ side x side is an off-highway vehicle only, and is not designed, equipped or manufactured for use on public streets, roads or highways. Obey the laws and regulations that control the use of your vehicle. ©2024 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit [Kawasaki.com](https://www.kawasaki.com) for full product details.