MULE PRO-FXT™ 820 EPS





\$16,899



TIMBERLINE GREEN



POWER

Engine 4-stroke, 3-cylinder, DOHC, liquid-cooled, gas

Displacement

48.0 lb-ft @ 3,500 rpm **Maximum Torque**

Bore x Stroke 72.0 x 66.5mm

Compression Ratio 9.5:1

Fuel System DFI® with 34mm throttle body

Continuously Variable Transmission (CVT) with (H,L,N,R) **Transmission**

Selectable 2WD/4WD, shaft. Dual mode rear differential **Final Drive**

with differential lock

Engine Braking

Alternator Output 75 amp

(max)

Rear Brakes Dual disc, 1-piston caliper

Ground Clearance

Fuel Capacity 7.9 gal

Turning Radius 16.0 ft

Cargo Bed 42.7 x 53.7 x 11.0 in (3-person) / 22.0 x 53.7 x 11.0 in (6-**Dimensions (LxWxH)**

Independent, mechanical disc

person)

Cargo Bed Load Capacity

999 lb (3-person)/350 lb (6-person)/348 lb CA Model

Payload Capacity

Park Brake Type

1,616.3/1,263.5 lb CA Model

Seating Capacity 3-person (1 row), 6 person (2 row)

Towing Capacity 2,000 lb

Lighting (2) Halogen headlights

CAPABILITY

Front Suspension / **Wheel Travel**

Double wishbone / 8.7 in

Rear Suspension / Wheel Travel

Double wishbone/8.5 in (L)/8.7 in (R)

Front Tires

26 x 9-12, radial

Rear Tires

26 x 11-12, radial

Wheel Type

Steel

Steering

Rack-and-pinion w/ Electric Power Steering (EPS), Tilt

steering

Front Brakes

Dual disc, 2-piston caliper

DETAILS

Overall Length 133.3 in

Overall Width 64.0 in

Overall Height 77.6 in

Dry Weight 1,832.4/1,834.6 lb** CA Model

Curb Weight 1,911.7/1,913.9 lb* CA Model

Wheelbase 92.3 in

Instruments

Multi-function display includes digital speedometer, fuel gauge, odometer, hour meter, clock, dual trip meters, 2WD/4WD indicator, water temperature warning indicator, oil pressure warning indicator, fuel injection warning indicator, CVT warning indicator, neutral, reverse and

parking indicators, seatbelt reminder lamps

Color Choices Timberline Green

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). **Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). All MULE™ PRO Series side x side's Rollover Protective Structure (ROPS) meets the performance requirements of ISO 3471.

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear protective gear appropriate for the use of this vehicle. Never operate under the influence of drugs or alcohol. Protect the environment. The Kawasaki MULE™ side x side is an off- highway vehicle only, and is not designed, equipped or manufactured for use on public streets, roads or highways. Obey the laws and regulations that control the use of your vehicle. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit Kawasaki.com for full product details.