2025 NINJA[®] 500





MSRP NON-ABS \$5,299





METALLIC MATTE WHITISH SILVER/METALLIC MOONDUST GRAY



PASSION RED/METALLIC FLAT SPARK BLACK/ METALLIC MATTE DARK GRAY



METALLIC FLAT SPARK BLACK/METALLIC SPARK BLACK/ METALLIC MOONDUST GRAY



POWER		Front Brakes	Single 310mm semi-floating disc with 2-piston calipers (and ABS)
Engine	4-stroke, Parallel Twin, DOHC, liquid-cooled	Rear Brakes	Single 220mm disc with single-piston caliper (and ABS)
Displacement	451cc		
Bore x Stroke	70.0 x 58.6mm	DETAILS	
Compression Ratio	11.3:1	Frame Type	Trellis, high-tensile steel
Maximum Horsepower	51.0 hp1 @ 10,000 rpm	Rake/Trail	24.5°/3.6 in
Maximum Torque	31.7 lb-ft @ 7,500 rpm	Overall Length	78.5 in
Fuel System	DFI® with dual 32mm throttle bodies	Overall Width	28.7 in
Ignition	TCBI with Digital Advance	Overall Height	44.1 in
Transmission	6-speed	Ground Clearance	5.7 in
Final Drive	Sealed chain	Seat Height	30.9 in
Electronic Rider Aids	Economical Riding Indicator, Anti-lock Brake System (ABS only)	Dry Weight	344.0 lb** (ABS) / 346.2 lb** (ABS) 50-State Model, 339.6 lb** (non-ABS) / 341.8 lb** (non-ABS) 50-State Model
PERFORMANCE		Curb Weight	374.9 lb*(ABS) / 377.1 lb* (ABS) 50-State Model, 370.4 lb* (non-ABS) / 372.6 lb* (non-ABS) 50-State Model
Front Suspension / Wheel Travel	41mm hydraulic telescopic fork/4.7 in	Fuel Capacity	3.7 gal
		Wheelbase	54.1 in
Rear Suspension / Wheel Travel	Horizontal back-link with adjustable spring preload/5.1 in	Special Features	ERGO-FIT®, LCD Instrumentation with Smartphone Connectivity via RIDEOLOGY THE APP
Front Tire	110/70-17	Color Choices	Metallic Matte Whitish Silver/Metallic Moondust
Rear Tire	150/60-17		Gray, Passion Red/Metallic Flat Spark Black/Metallic Matte Dark Gray, Metallic Flat Spark Black/Metallic Spark Black/Metallic Moondust Gray

*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). When

Scan with camera to view videos, key features and more.



equipped, California evaporative emissions equipment adds approximately 2.2 lb.

**Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). 1This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard.

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2024 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit Kawasaki.com for full product details.