

2025

NINJA® 500 SE ABS

Kawasaki

Let the Good Times Roll®



MSRP

\$6,399



METALLIC FLAT SPARK BLACK/METALLIC SPARK BLACK/
METALLIC MOONDUST GRAY



PASSION RED/METALLIC FLAT SPARK BLACK/
METALLIC MATTE DARK GRAY



POWER		Rear Tire	150/60-17
Engine	4-stroke, Parallel Twin, DOHC, liquid-cooled	Front Brakes	Single 310mm semi-floating disc with 2-piston calipers and ABS
Displacement	451cc	Rear Brakes	Single 220mm disc with single-piston caliper and ABS
Bore x Stroke	70.0 x 58.6mm	DETAILS	
Compression Ratio	11.3:1	Frame Type	Trellis, high-tensile steel
Maximum Horsepower	51.0 hp ¹ @ 10,000 rpm	Rake/Trail	24.7° / 3.6 in
Maximum Torque	31.7 lb-ft @ 7,500 rpm	Overall Length	78.5 in
Fuel System	DFI® with dual 32mm throttle bodies	Overall Width	28.7 in
Ignition	TCBI with Digital Advance	Overall Height	46.5 in
Transmission	6-speed	Ground Clearance	5.7 in
Final Drive	Sealed chain	Seat Height	30.9 in
Electronic Rider Aids	Economical Riding Indicator, Anti-lock Brake System (ABS)	Dry Weight	348.4 lb** / 350.6 lb** 50-State Model
PERFORMANCE		Curb Weight	379.3 lb* / 381.5 lb* 50-State Model
Front Suspension / Wheel Travel	41mm hydraulic telescopic fork/4.7 in	Fuel Capacity	3.7 gal
Rear Suspension / Wheel Travel	Horizontal back-link with adjustable spring preload/5.1 in	Wheelbase	54.1 in
Front Tire	110/70-17	Special Features	ERGO-FIT®, Full-color TFT Instrumentation with Smartphone Connectivity via RIDEOLOGY THE APP, Kawasaki's Intelligent Proximity Activation Start System (KIPASS), USB-C outlet
		Color Choices	Metallic Flat Spark Black/Metallic Spark Black/ Metallic Moondust Gray, Passion Red/Metallic Flat Spark Black/Metallic Matte Dark Gray

Scan with camera
to view videos,
key features
and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). When equipped, California evaporative emissions equipment adds approximately 2.2 lb.

**Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

¹This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard.

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2024 Kawasaki Motors Corp., U.S.A.

Specifications subject to change. Visit [Kawasaki.com](https://www.kawasaki.com) for full product details.