

2025

# NINJA<sup>®</sup> ZX<sup>™</sup> -10R

**Kawasaki**  
Let the Good Times Roll<sup>®</sup>



MSRP NON-ABS  
**\$17,799**

MSRP ABS  
**\$18,799**

 METALLIC FLAT SPARK BLACK/EBONY



## POWER

|                       |   |
|-----------------------|---|
| Engine                | 4-stroke, in-line 4-cylinder, DOHC, 16-valve, liquid-cooled   |
| Displacement          | 998cc   |
| Bore x Stroke         | 76.0 x 55.0mm   |
| Compression Ratio     | 13.0:1  |
| Maximum Horsepower    | 196.0 hp <sup>1</sup> @ 11,500 rpm  |
| Maximum Torque        | 83.9 lb-ft @ 11,300 rpm   |
| Fuel System           | DFI <sup>®</sup> , 47mm throttle bodies   |
| Ignition              | TCBI with electronic advance  |
| Transmission          | 6-speed   |
| Final Drive           | Sealed chain  |
| Electronic Rider Aids | Öhlins Electronic Steering Damper, Electronic Cruise Control, Kawasaki Launch Control Mode (KLCM), Kawasaki Intelligent anti-lock Brake System (KIBS) (ABS only), Sport-Kawasaki TRaction Control (S-KTRC), Kawasaki Engine Braking Control, Kawasaki Quick Shifter (KQS) (upshift & downshift), Kawasaki Corner Management Function (KCMF) |

## PERFORMANCE

|                                 |   |
|---------------------------------|---|
| Front Suspension / Wheel Travel | 43mm inverted Showa Balance Free Fork (BFF), adjustable stepless rebound and compression damping, spring preload adjustability/4.7 in |
|---------------------------------|---|

|                                |   |
|--------------------------------|---|
| Rear Suspension / Wheel Travel | Horizontal back-link with Showa Balance Free Rear Cushion (BFRC) lite shock, stepless, dual-range (low-/high-speed) compression damping, stepless rebound damping, fully adjustable spring preload/4.5 in |
| Front Tire                     | 120/70 ZR17   |
| Rear Tire                      | 190/55 ZR17   |
| Front Brakes                   | Brembo dual semi-floating 330mm discs with dual radial mounted monobloc 4-piston calipers, Kawasaki Intelligent anti-lock Brake System (KIBS) (ABS only)  |
| Rear Brakes                    | Single 220mm disc with aluminum single-piston caliper, Kawasaki Intelligent anti-lock Brake System (KIBS) (ABS only)  |

## DETAILS

|                  |   |
|------------------|---|
| Frame Type       | Aluminum perimeter  |
| Rake/Trail       | 25.0° / 4.1 in  |
| Overall Length   | 82.1 in   |
| Overall Width    | 29.5 in   |
| Overall Height   | 46.7 in   |
| Ground Clearance | 5.3 in  |
| Seat Height      | 32.9 in   |
| Curb Weight      | 456.4 lb* (ABS), 452.0 lb* (non-ABS)  |
| Fuel Capacity    | 4.5 gal   |
| Wheelbase        | 57.1 in   |
| Special Features | 4.3" Full-Color TFT Instrumentation, Smartphone Connectivity via RIDEOLGY THE APP |
| Color Choices    | Metallic Flat Spark Black/Ebony   |

Scan with camera to view videos, key features and more.



\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). When equipped, California evaporative emissions equipment adds approximately 2.2 lb.

<sup>1</sup>This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard.

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A.

Specifications subject to change. Visit [Kawasaki.com](http://Kawasaki.com) for full product details.