

2025

NINJA® ZX™ -10R

Kawasaki
Let the Good Times Roll®



MSRP NON-ABS
\$17,799

MSRP ABS
\$18,799

 METALLIC FLAT SPARK BLACK/EBONY



POWER

Engine	4-stroke, in-line 4-cylinder, DOHC, 16-valve, liquid-cooled
Displacement	998cc
Bore x Stroke	76.0 x 55.0mm
Compression Ratio	13.0:1
Maximum Horsepower	196.0 hp ¹ @ 11,500 rpm
Maximum Torque	83.9 lb-ft @ 11,300 rpm
Fuel System	DFI®, 47mm throttle bodies
Ignition	TCBI with electronic advance
Transmission	6-speed
Final Drive	Sealed chain
Electronic Rider Aids	Öhlins Electronic Steering Damper, Electronic Cruise Control, Kawasaki Launch Control Mode (KLCM), Kawasaki Intelligent anti-lock Brake System (KIBS) (ABS only), Sport-Kawasaki TRaction Control (S-KTRC), Kawasaki Engine Braking Control, Kawasaki Quick Shifter (KQS) (upshift & downshift), Kawasaki Corner Management Function (KCMF)

PERFORMANCE

Front Suspension / Wheel Travel	43mm inverted Showa Balance Free Fork (BFF), adjustable stepless rebound and compression damping, spring preload adjustability/4.7 in
---------------------------------	---------------------------------------------------------------------------------------------------------------------------------------

Rear Suspension / Wheel Travel	Horizontal back-link with Showa Balance Free Rear Cushion (BFRC) lite shock, stepless, dual-range (low-/high-speed) compression damping, stepless rebound damping, fully adjustable spring preload/4.5 in
Front Tire	120/70 ZR17
Rear Tire	190/55 ZR17
Front Brakes	Brembo dual semi-floating 330mm discs with dual radial mounted monobloc 4-piston calipers, Kawasaki Intelligent anti-lock Brake System (KIBS) (ABS only)
Rear Brakes	Single 220mm disc with aluminum single-piston caliper, Kawasaki Intelligent anti-lock Brake System (KIBS) (ABS only)

DETAILS

Frame Type	Aluminum perimeter
Rake/Trail	25.0° / 4.1 in
Overall Length	82.1 in
Overall Width	29.5 in
Overall Height	46.7 in
Ground Clearance	5.3 in
Seat Height	32.9 in
Curb Weight	456.4 lb* (ABS), 452.0 lb* (non-ABS)
Fuel Capacity	4.5 gal
Wheelbase	57.1 in
Special Features	4.3" Full-Color TFT Instrumentation, Smartphone Connectivity via RIDEOLGY THE APP
Color Choices	Metallic Flat Spark Black/Ebony

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). When equipped, California evaporative emissions equipment adds approximately 2.2 lb.

¹This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard.

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit Kawasaki.com for full product details.