## **ALL-NEW 2025**

# RIDGE® CREW HVAC CAMO





MSRP **\$31,799** 



TRUETIMBER® STRATA

12.9 gal

19.0 ft

2,500 lb

All-LED lighting

34.6 x 49.0 x 12.8 in

1,000/600 lb CA Model

1,444/1,290 lb CA Model

6-person (2 row), bench seats



13.2/13.8 in (max preload); 13.2 in CA Model

#### **POWER**

Engine 4-stroke, DOHC, 4-valve, in-line 4-cylinder, liquid-cooled

Displacement 999cc

 Maximum Horsepower
 92.0 hp¹ @ 8,500 rpm

 Maximum Torque
 65.8 lb-ft @ 5,500 rpm

Bore x Stroke 73.4 x 59.0mm

Compression Ratio 10.6:1
Fuel System EFI

Ignition TCBI with Digital Advance

Starting System Electric

Transmission Continuously Variable Transmission (CVT) with (H,L,N,R)

Final Drive Selectable 4WD with locking rear differential, shaft

Engine Braking

Alternator Output (max)

Electronic Rider Aids

85 amp

Yes

Power Modes, Economical Riding Indicator

### **DETAILS**

Lighting

**Ground Clearance** 

**Fuel Capacity** 

**Turning Radius** 

Cargo Bed Load

**Payload Capacity** 

**Seating Capacity** 

**Towing Capacity** 

(LxWxH)

Capacity

**Cargo Bed Dimensions** 

Frame Ladder type, tubular steel

Overall Length 155.3 in
Overall Width 64.0 in
Overall Height 81.5 in

 Dry Weight
 2,368.2/2,370.4 lb\*\* CA Model

 Curb Weight
 2,478.4/2,480.6 lb\* CA Model

Wheelbase 122.2 i

Instruments Digital speedometer, tachometer, fuel gauge, odometer, dual

trip meters, total time, trip time, average speed, gear indicator, Driving Mode, Power Mode, clock, water temperature, battery voltage, oil change reminder, Economical Riding Indicator, maintenance reminder, high beam, neutral, reverse, and warning lights (battery, EPS, CVT, seatbelt, parking indicator, oil

pressure, water temperature)

Additional Features

Color Choices

Full Cab with HVAC, Adjustable driver's seat, ERGO-FIT®, Full-color TFT Instrumentation with Smartphone Connectivity via RIDEOLOGY THE APP Powersports, USB ports, KQR™ system

compatible

TRUETIMBER® STRATA

#### **CAPABILITY**

Front Suspension / Wheel Travel Long-Travel, Double Wishbone/12.7 in

Rear Suspension / Wheel Travel

Wheel Type

Long-Travel, Double Wishbone/12.7 in

 Front Tires
 Duro 27 x 9-14

 Rear Tires
 Duro 27 x 11-14

Steering Rack-and-pinion w/ Electric Power Steering (EPS)

14" Aluminum

Front Brakes Dual hydraulic 249mm discs with two-piston calipers

Rear Brakes Dual hydraulic 249mm discs with single-piston calipers

Scan with camera to view videos, key features and more



\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

\*\*Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard.

Specifications subject to change. Visit Kawasaki.com for full product details.