

2025

# VERSYS® -X 300 ABS

**Kawasaki**  
Let the Good Times Roll®

MSRP  
**\$6,199**

 CANDY LIME GREEN/METALLIC FLAT SPARK BLACK



## POWER

Engine	4-stroke, 2-cylinder, DOHC, liquid-cooled
Displacement	296cc
Bore x Stroke	62.0 x 49.0mm
Compression Ratio	10.6:1
Maximum Torque	19.2 lb-ft @ 10,000 rpm
Fuel System	DFI® with 32mm throttle bodies (2)
Ignition	TCBI with Digital Advance
Transmission	6-speed, return shift with wet multi-disc manual clutch
Final Drive	Chain
Electronic Rider Aids	Economical Riding Indicator, Anti-lock Brake System (ABS)

## PERFORMANCE

Front Suspension / Wheel Travel	41mm telescopic fork/5.1 in
Rear Suspension / Wheel Travel	Uni-Trak® swingarm with 5-way spring preload adjustment/5.8 in

Front Tire	100/90-19
Rear Tire	130/80-17
Front Brakes	Single 290mm disc, ABS
Rear Brakes	Single 220mm disc, ABS

## DETAILS

Frame Type	Tubular, diamond
Rake/Trail	24.3° / 4.3 in
Overall Length	85.4 in
Overall Width	33.9 in
Overall Height	54.7 in
Ground Clearance	7.1 in
Seat Height	32.1 in
Dry Weight	350.6 lb**
Curb Weight	385.9 lb*
Fuel Capacity	4.5 gal
Wheelbase	57.1 in
Special Features	ERGO-FIT®
Color Choices	Candy Lime Green/Metallic Flat Spark Black

Scan with camera to view videos, key features and more.



\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). When equipped, California evaporative emissions equipment adds approximately 2.2 lb.  
\*\*Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).  
KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2024 Kawasaki Motors Corp., U.S.A.  
Specifications subject to change. Visit [Kawasaki.com](http://Kawasaki.com) for full product details.