



2025 VULCAN® S

Kawasaki
Let the Good Times Roll®



MSRP NON-ABS
\$7,399

MSRP ABS
\$7,899

-  METALLIC MATTE GRAPHITE GRAY/
METALLIC MATTE CARBON GRAY
-  METALLIC FLAT SPARK BLACK



POWER

| | |
|------------------------------|--------------------------------------------------------------|
| Engine | 4-stroke, 2-cylinder, DOHC, liquid-cooled |
| Displacement | 649cc |
| Bore x Stroke | 83.0 x 60.0mm |
| Compression Ratio | 10.8:1 |
| Maximum Torque | 46.3 lb-ft @ 6,600 rpm |
| Fuel System | DFI® with 38mm throttle bodies (2), with sub-throttle valves |
| Ignition | TCBI with Electronic Advance |
| Transmission | 6-speed with positive neutral finder |
| Final Drive | Sealed chain |
| Electronic Rider Aids | Economical Riding Indicator, Anti-lock Brake System (ABS) |

| | |
|---------------------|--------------------------------------------------------|
| Front Tire | 120/70-18 |
| Rear Tire | 160/60-17 |
| Front Brakes | Single 300mm disc with twin-piston caliper (and ABS) |
| Rear Brakes | Single 250mm disc with single-piston caliper (and ABS) |

PERFORMANCE

| | |
|----------------------------------------|-----------------------------------------------------------------------|
| Front Suspension / Wheel Travel | 41mm telescopic fork/5.1 in |
| Rear Suspension / Wheel Travel | Lay-down offset rear shock with linkage and adjustable preload/3.2 in |

DETAILS

| | |
|-------------------------|------------------------------------------------------------------------------------|
| Frame Type | High-tensile steel diamond frame |
| Rake/Trail | 31° / 4.7 in |
| Overall Length | 90.9 in |
| Overall Width | 34.6 in |
| Overall Height | 43.3 in |
| Ground Clearance | 5.1 in |
| Seat Height | 27.8 in |
| Curb Weight | 498.3 lb* (ABS), 491.7 lb* (non-ABS) |
| Fuel Capacity | 3.7 gal |
| Wheelbase | 62.0 in |
| Special Features | ERGO-FIT® |
| Color Choices | Metallic Matte Graphite Gray/Metallic Matte Carbon Gray, Metallic Flat Spark Black |

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). When equipped, California evaporative emissions equipment adds approximately 2.2 lb.
KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2024 Kawasaki Motors Corp., U.S.A.
Specifications subject to change. Visit [Kawasaki.com](https://www.kawasaki.com) for full product details.